Fillmore County, Minnesota

[Data apply to the entire extent of the map unit within the survey area. Map unit and soil properties for a specific parcel of land may vary somewhat and should be determined by onsite investigation]

1010--Pits, quarry

Pits, quarry

Extent: 100 percent of the unit Soil loss tolerance (T factor):

Landform(s): hills, valley sides Wind erodibility group (WEG):

Slope gradient: Wind erodibility index (WEI):
Parent material: Kw factor (surface layer)

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated:

Flooding: Hydric soil: no
Ponding: Hydrologic group:

Drainage class: Potential for frost action:

Representative soil profile: Texture Permeability Available water capacity pH

1054--Udorthents, loamy (abandoned iron mine), 0 to 25 percent slopes

Udorthents, loamy

Extent: 70 to 99 percent of the unit Soil loss tolerance (T factor):

Landform(s): till plains Wind erodibility group (WEG):

Slope gradient: 0 to 25 percent

Wind erodibility index (WEI):

Parent material: loamy material

Kw factor (surface layer)

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated:

Flooding: Hydric soil:

Ponding: Hydrologic group:

Drainage class: well drained Potential for frost action:

Representative soil profile:

Texture

Permeability

Available water
capacity

pH



Available water

Fillmore County, Minnesota

Aa--Alluvial land, medium textured, poorly drained

Alluvial land, medium textured, frequently flooded

Extent: 85 percent of the unit

Landform(s): flood plains

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 6

Slope gradient: 0 to 2 percent

Wind erodibility index (WEI): 48

Parent material: loamy alluvium

Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2w

Flooding: frequent

Hydric soil: yes

Ponding: frequent

Hydrologic group: B/D

Drainage class: poorly drained Potential for frost action: high

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Α	0 to 28 in	silt loam	moderate	6.15 to 6.71 in	6.1 to 7.8
AC 2	28 to 39 in	silt loam	moderate	1.87 to 2.43 in	6.1 to 7.8
C 3	9 to 60 in	silt loam	moderate	3.13 to 4.17 in	6.1 to 8.4

Ab--Alluvial land, medium textured, well drained

Alluvial land, medium textured, occasionally flooded

Extent: 85 percent of the unit

Landform(s): flood plains

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 4L

Slope gradient: 0 to 2 percent

Wind erodibility index (WEI): 86

Parent material: loamy alluvium

Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2w

Flooding: occasional

Hydric soil: no

Ponding: none Hydrologic group: B/D

Drainage class: moderately well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 26 in	silt loam	moderate	5.46 to 5.98 in	6.6 to 8.4
C 26 to 60 in	silty clay loam	moderate	6.43 to 7.11 in	6.1 to 7.8



Fillmore County, Minnesota

Ac--Alluvial land, coarse textured, well drained

Alluvial land, coarse textured, occasionally flooded

Extent: 85 percent of the unit

Landform(s): flood plains

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 2

Slope gradient: 0 to 2 percent

Wind erodibility index (WEI): 134

Parent material: sandy alluvium

Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3s

Flooding: occasional Hydric soil: no

Ponding: none Hydrologic group: A/D

Drainage class: moderately well drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	capacity	pН
A 0 to 8 in	loamy fine sand	rapid	0.79 to 0.94 in	5.6 to 7.8
AC 8 to 40 in	loamy sand	rapid	3.23 to 3.87 in	5.6 to 7.8
C1 40 to 50 in	sand	rapid	0.59 to 1.08 in	6.1 to 7.8
C2 50 to 60 in	sand	rapid	0.20 to 0.69 in	6.1 to 7.8



A. . . : ! - b ! - . . . - t - . . .

Fillmore County, Minnesota

Ca--Chaseburg and Judson silt loams, 0 to 1 percent slopes

Chaseburg, frequently flooded

Extent: 45 percent of the unit

Landform(s): drainageways

Slope gradient: 0 to 1 percent

Parent material: alluvium and/or colluvium

Restrictive feature(s): greater than 60 inches

Flooding: frequent Ponding: none

Drainage class: well drained

Soil loss tolerance (T factor): 5
Wind erodibility group (WEG): 5
Wind erodibility index (WEI): 56
Kw factor (surface layer) .43
Land capability, nonirrigated: 1

Hydric soil: no Hydrologic group: B/D

Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	6.1 to 7.8
C 10 to 60 in	silt loam	moderate	9.00 to 11.00 in	5.6 to 7.8

Judson, frequently flooded

Extent: 45 percent of the unit

Landform(s): drainageways

Slope gradient: 0 to 1 percent

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 6

Wind erodibility index (WEI): 48

Parent material: alluvium and/or colluvium

Kw factor (surface layer) .28

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 1

Flooding: frequent


Hydric soil: no

Ponding: none

Hydrologic group: B/D

Drainage class: moderately well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 25 in	silt loam	moderate	5.29 to 5.80 in	5.6 to 7.3
A 25 to 48 in	silty clay loam	moderate	4.80 to 5.25 in	5.6 to 7.3
C 48 to 60 in	silt loam	moderate	2.48 to 2.72 in	6.1 to 7.8



Fillmore County, Minnesota

Cb--Chaseburg and Judson silt loams, 2 to 6 percent slopes

Chaseburg, very rarely flooded

Extent: 45 percent of the unit

Landform(s): drainageways

Slope gradient: 2 to 6 percent

Parent material: alluvium and/or colluvium Restrictive feature(s): greater than 60 inches

Flooding: very rare Ponding: none

Drainage class: well drained

Soil loss tolerance (T factor): 5
Wind erodibility group (WEG): 5

Wind erodibility index (WEI): 56
Kw factor (surface layer) .43

Land capability, nonirrigated: 2e

Hydric soil: no Hydrologic group: B

Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	6.1 to 7.8
C 10 to 60 in	silt loam	moderate	9.00 to 11.00 in	5.6 to 7.8

Judson, very rarely flooded

Extent: 45 percent of the unit Landform(s): drainageways Slope gradient: 2 to 6 percent

Parent material: alluvium and/or colluvium Restrictive feature(s): greater than 60 inches

Flooding: very rare Ponding: none

Drainage class: moderately well drained

Soil loss tolerance (T factor): 5 Wind erodibility group (WEG): 6

Wind erodibility index (WEI): 48
Kw factor (surface layer) .28
Land capability, nonirrigated: 2e

Hydric soil: no Hydrologic group: B

Potential for frost action: high

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Ap	0 to 25 in	silt loam	moderate	5.29 to 5.80 in	5.6 to 7.3
A 2	5 to 48 in	silty clay loam	moderate	4.80 to 5.25 in	5.6 to 7.3
C 4	8 to 72 in	silt loam	moderate	5.04 to 5.52 in	6.1 to 7.8



Fillmore County, Minnesota

Cc--Chelsea and Boone loamy fine sands, 2 to 6 percent slopes

Chelsea

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient:2 to 6 percentWind erodibility index (WEI): 134Parent material:eolian sandsKw factor (surface layer).10

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 4s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative	soil profile:	Texture	Permeability	capacity	рН
Α	0 to 8 in	loamy fine sand	rapid	0.79 to 1.18 in	5.6 to 7.3
E&Bt	8 to 60 in	fine sand	rapid	3.12 to 4.16 in	5.1 to 6.5

Boone

Extent: 45 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient:2 to 6 percentWind erodibility index (WEI):134Parent material:sandy residuumKw factor (surface layer).24

Restrictive feature(s): paralithic bedrock at 20 to 40 inche

Land capability, nonirrigated: 4s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 3 in	loamy fine sand	rapid	0.31 to 0.41 in	3.5 to 7.3
B 3 to 10 in	loamy fine sand	rapid	0.20 to 0.80 in	3.5 to 7.3
C 10 to 30 in	fine sand	rapid	0.40 to 2.21 in	4.5 to 6.5
2R 30 to 60 in	weathered bedrock	moderate		



Fillmore County, Minnesota

Cd--Chelsea and Boone loamy fine sands, 7 to 11 percent slopes

Chelsea

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 134

Parent material: eolian sands Kw factor (surface layer) .10

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 6s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative so	oil profile:	Texture	Permeability	Available water capacity	рН
A 0	to 8 in	loamy fine sand	rapid	0.79 to 1.18 in	5.6 to 7.3
E&Bt 8	to 60 in	fine sand	rapid	3.12 to 4.16 in	5.1 to 6.5

Boone

Extent: 45 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 134

Parent material: sandy residuum Kw factor (surface layer) .24

Restrictive feature(s): paralithic bedrock at 20 to 40 inche

Land capability, nonirrigated: 6s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 3 in	loamy fine sand	rapid	0.31 to 0.41 in	3.5 to 7.3
B 3 to 10 in	sand	rapid	0.20 to 0.80 in	3.5 to 7.3
C 10 to 30 in	fine sand	rapid	0.40 to 2.21 in	4.5 to 6.5
2R 30 to 60 in	weathered bedrock	moderate		



Fillmore County, Minnesota

Ce--Chelsea and Boone loamy fine sands, 12 to 17 percent slopes

Chelsea

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 134

Parent material: eolian sands Kw factor (surface layer) .10

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative	soil profile:	Texture	Permeability	capacity	рН
A	0 to 8 in	loamy fine sand	rapid	0.79 to 1.18 in	5.6 to 7.3
E&Bt	8 to 60 in	fine sand	rapid	3.12 to 4.16 in	5.1 to 6.5

Boone

Extent: 45 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient:12 to 17 percentWind erodibility index (WEI):134Parent material:sandy residuumKw factor (surface layer).24

Restrictive feature(s): paralithic bedrock at 20 to 40 inche

Land capability, nonirrigated: 7s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 3 in	loamy fine sand	rapid	0.31 to 0.41 in	3.5 to 7.3
B 3 to 10 in	sand	rapid	0.20 to 0.80 in	3.5 to 7.3
C 10 to 30 in	fine sand	rapid	0.40 to 2.21 in	4.5 to 6.5
2R 30 to 60 in	weathered bedrock	moderate		



Available water

Fillmore County, Minnesota

Cf--Chelsea and Boone loamy fine sands, 18 to 35 percent slopes

Chelsea

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient: 18 to 35 percent Wind erodibility index (WEI): 134

Parent material: eolian sands Kw factor (surface layer) .10

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative so	oil profile:	Texture	Permeability	Available water capacity	рН
A 0	to 8 in	loamy fine sand	rapid	0.79 to 1.18 in	5.6 to 7.3
E&Bt 8	to 60 in	fine sand	rapid	3.12 to 4.16 in	5.1 to 6.5

Boone

Extent: 45 percent of the unit Soil loss tolerance (T factor): 4

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient: 18 to 35 percent Wind erodibility index (WEI): 134

Parent material: sandy residuum

Kw factor (surface layer) .15

Restrictive feature(s): paralithic bedrock at 40 to 70 inche

Land capability, nonirrigated: 7s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative soil profile	: Texture	Permeability	Available water capacity	рН
A 0 to 16 in	loamy fine sand	rapid	1.61 to 2.26 in	3.5 to 7.3
B 16 to 42 in	sand	rapid	1.04 to 2.08 in	3.5 to 7.3
2R 42 to 60 in	weathered bedrock	moderate		



Fillmore County, Minnesota

Cg--Clyde silty clay loam

Clyde

Extent: 85 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): flats Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 48

Parent material: till Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3w

Flooding: none Hydric soil: yes
Ponding: none Hydrologic group: B/D

Drainage class: very poorly drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 18 in	silty clay loam	moderate	3.80 to 4.17 in	6.1 to 7.3
Bg 18 to 25 in	clay loam	moderate	1.28 to 1.42 in	6.1 to 7.3
2Cg1 25 to 44 in	gravelly sandy loam	moderately rapid	1.51 to 2.46 in	6.1 to 7.3
2Ca2 44 to 60 in	sandy clay loam	moderate	2.68 to 2.99 in	6.6 to 8.4



Fillmore County, Minnesota

Ch--Clyde silty clay loam, overwash

Clyde, overwash

Extent: 85 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): flats Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 48

Parent material: till Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 3w

Flooding: none Hydric soil: yes
Ponding: none Hydrologic group: B/D

Drainage class: very poorly drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 24 in	silty clay loam	moderate	5.04 to 5.52 in	6.1 to 7.3
Bg 24 to 40 in	silty clay loam	moderate	2.91 to 3.23 in	6.1 to 7.3
Cg1 40 to 50 in	sandy loam	moderately rapid	0.79 to 1.28 in	6.1 to 7.3
2Cg2 50 to 60 in	sandy clay loam	moderate	1.67 to 1.87 in	6.6 to 8.4

Da--Dakota fine sandy loam, 0 to 1 percent slopes

Dakota

Extent: 85 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): terraces Wind erodibility group (WEG): 3
Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 86

Parent material: outwash Kw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Representative soil pro	ofile: Texture	Permeability	Available water capacity	рН
Ap 0 to 13	in fine sandy loam	moderately rapid	1.56 to 1.95 in	5.6 to 7.3
Bt1 13 to 28	in loam	moderately rapid	2.24 to 2.84 in	5.1 to 6.0
2Bt2 28 to 60	in sand	very rapid	0.64 to 1.91 in	5.1 to 6.5



Fillmore County, Minnesota

Db--Dakota fine sandy loam, 2 to 6 percent slopes

Dakota

Extent: 85 percent of the unit

Soil loss tolerance (T factor): 3

Landform(s): terraces Wind erodibility group (WEG): 3
Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 86

Parent material: outwash Kw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none

Hydric soil: no

Ponding: none Hydrologic group: A

Drainage class: well drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 13 in	fine sandy loam	moderately rapid	1.56 to 1.95 in	5.6 to 7.3
Bt1 13 to 28 in	loam	moderately rapid	2.24 to 2.84 in	5.1 to 6.0
2Bt2 28 to 60 in	gravelly coarse sand	very rapid	0.64 to 1.91 in	5.1 to 6.5

Dd--Dakota fine sandy loam, 12 to 17 percent slopes, moderately eroded

Dakota, moderately eroded

Extent: 85 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): terraces Wind erodibility group (WEG): 3
Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 86

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7s


Flooding: none

Hydric soil: no

Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative soil p	orofile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 6	6 in fine sandy lo	oam	moderately rapid	0.71 to 0.89 in	5.6 to 7.3
Bt1 6 to 1	13 in sandy loam		moderately rapid	0.71 to 0.85 in	4.5 to 6.0
2Bt2 13 to 2	28 in gravelly loar	ny sand	very rapid	0.30 to 0.60 in	4.5 to 6.0
2C 28 to 6	60 in gravelly loar	ny sand	very rapid	0.64 to 1.28 in	4.5 to 6.0



Fillmore County, Minnesota

De--Dakota loam, 0 to 1 percent slopes

Dakota

Extent: 90 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): terraces Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 48

Parent material: outwash

Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 2s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil	profile:	Texture	Permeability	Available water capacity	рН
A 0 to	14 in loam		moderate	2.83 to 3.12 in	5.1 to 7.3
Bt1 14 to	27 in loam		moderate	1.89 to 2.39 in	5.1 to 7.3
2Bt2 27 to	36 in sandy loam		moderately rapid	0.18 to 1.27 in	5.1 to 7.3
2C 36 to	60 in gravelly coars	se sand	rapid	0.48 to 2.40 in	5.1 to 7.8

Fillmore County, Minnesota

Df--Dakota loam, 2 to 6 percent slopes

Dakota

Extent: 90 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): terraces Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: outwash Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative so	il profile:	Texture	Permeability	Available water capacity	рН
A 0 t	o 14 in	loam	moderate	2.83 to 3.12 in	5.1 to 7.3
Bt1 14 t	o 27 in	loam	moderate	1.89 to 2.39 in	5.1 to 7.3
2Bt2 27 t	o 36 in	sandy loam	moderately rapid	0.18 to 1.27 in	5.1 to 7.3
2C 36 t	o 60 in	gravelly coarse sand	rapid	0.48 to 2.40 in	5.1 to 7.8

Fillmore County, Minnesota

Dg--Dickinson fine sandy loam, 0 to 6 percent slopes

Dickinson

Extent: 90 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): terraces Wind erodibility group (WEG): 3

Slope gradient: 0 to 6 percent

Wind erodibility index (WEI): 86

Parent material: eolian deposits

Kw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches


Land capability, nonirrigated: 3e

Flooding: none

Hydric soil: no

Ponding: none Hydrologic group: A

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	fine sandy loam	moderately rapid	1.09 to 1.36 in	5.6 to 7.3
Bw 9 to 30 in	fine sandy loam	moderately rapid	2.50 to 3.13 in	5.1 to 6.5
BC 30 to 36 in	loamy fine sand	rapid	0.47 to 0.59 in	5.1 to 6.5
C 36 to 60 in	fine sand	rapid	0.48 to 0.96 in	5.6 to 7.3



Fillmore County, Minnesota

Dh--Dickinson fine sandy loam, 2 to 6 percent slopes

Dickinson

Extent: 90 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): terraces Wind erodibility group (WEG): 3

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 86

Parent material: eolian deposits

Kw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none

Hydric soil: no

Ponding: none Hydrologic group: A

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	fine sandy loam	moderately rapid	1.09 to 1.36 in	5.6 to 7.3
Bw 9 to 30 in	fine sandy loam	moderately rapid	2.50 to 3.13 in	5.1 to 6.5
BC 30 to 36 in	loamy fine sand	rapid	0.47 to 0.59 in	5.1 to 6.5
C 36 to 60 in	fine sand	rapid	0.48 to 0.96 in	5.6 to 7.3

Fillmore County, Minnesota

Dk--Dickinson fine sandy loam, 7 to 11 percent slopes, moderately eroded

Dickinson, moderately eroded

Extent: 90 percent of the unit

Landform(s): terraces

Soil loss tolerance (T factor): 3

Wind erodibility group (WEG): 3

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 86
Parent material: eolian deposits Kw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: well drained Potential for frost action: moderate

Representative	soil profile:	Texture	Permeability	capacity	pН
Ap	0 to 9 in	fine sandy loam	moderately rapid	1.09 to 1.36 in	5.6 to 7.3
Bw	9 to 30 in	fine sandy loam	moderately rapid	2.50 to 3.13 in	5.1 to 6.5
BC 3	0 to 36 in	loamy sand	rapid	0.47 to 0.59 in	5.1 to 6.5
C 3	6 to 60 in	sand	rapid	0.48 to 0.96 in	5.6 to 7.3

DI--Dickinson fine sandy loam, loamy substratum, 2 to 6 percent slopes

Dickinson, loamy substratum

Extent: 90 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): terracesWind erodibility group (WEG): 3Slope gradient: 2 to 6 percentWind erodibility index (WEI): 86Parent material: eolian depositsKw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: well drained Potential for frost action: moderate

Representative soil profile	Texture	Permeability	Available water capacity	рН
Ap 0 to 20 in	fine sandy loam	moderately rapid	2.41 to 3.01 in	5.6 to 7.3
Bw 20 to 42 in	fine sandy loam	rapid	1.76 to 2.20 in	5.1 to 6.0
C 42 to 60 in	loam	moderate	3.01 to 3.37 in	5.6 to 6.5



This report shows only the major soils in each map unit

A. . . : ! - b ! - . . . - t - . . .

Fillmore County, Minnesota

Dn--Dickinson fine sandy loam, loamy substratum, 7 to 11 percent slopes, moderately eroded

Dickinson, loamy substratum, moderately eroded

Extent: 90 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): terracesWind erodibility group (WEG): 3Slope gradient: 7 to 11 percentWind erodibility index (WEI): 86Parent material: eolian depositsKw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Ар	0 to 20 in	fine sandy loam	moderately rapid	2.41 to 3.01 in	5.6 to 7.3
Bw 2	20 to 42 in	fine sandy loam	rapid	1.76 to 2.20 in	5.1 to 6.0
C 4	42 to 60 in	loam	moderate	3.01 to 3.37 in	5.6 to 6.5



Fillmore County, Minnesota

Do--Dickinson loam, 2 to 6 percent slopes

Dickinson

Extent: 90 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): terraces Wind erodibility group (WEG): 5

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 56

Parent material: eolian deposits Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Representative soil profile	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	loam	moderately rapid	1.09 to 1.36 in	5.6 to 7.3
Bw 9 to 30 in	fine sandy loam	moderately rapid	2.50 to 3.13 in	5.1 to 6.5
BC 30 to 36 in	loamy fine sand	rapid	0.47 to 0.59 in	5.1 to 6.5
C 36 to 60 in	fine sand	rapid	0.48 to 0.96 in	5.6 to 7.3

Fillmore County, Minnesota

Dr--Dickinson loam, 7 to 11 percent slopes, moderately eroded

Dickinson, moderately eroded

Extent: 90 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): terraces Wind erodibility group (WEG): 5

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 56

Parent material: eolian deposits Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 4e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Representative soil profile	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	loam	moderately rapid	1.09 to 1.36 in	5.6 to 7.3
Bw 9 to 20 in	fine sandy loam	moderately rapid	1.32 to 1.65 in	5.6 to 7.3
BC 20 to 30 in	fine sandy loam	moderately rapid	1.18 to 1.48 in	5.1 to 6.5
C1 30 to 36 in	loamy fine sand	rapid	0.47 to 0.59 in	5.1 to 6.5
C2 36 to 60 in	sand	rapid	0.48 to 0.96 in	5.6 to 6.5



Fillmore County, Minnesota

Ds--Dubuque and Whalan silt loams, 2 to 6 percent slopes

Dubuque

Extent: 45 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: loess over limestone residuum Kw factor (surface layer) .43

Restrictive feature(s): lithic bedrock at 20 to 30 inches

Land capability, nonirrigated: 2e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: D

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 3 in	silt loam	moderate	0.63 to 0.69 in	5.1 to 7.3
E 3 to 12 in	silt loam	moderate	1.56 to 1.73 in	5.1 to 6.0
Bt1 12 to 20 in	silty clay loam	slow	0.99 to 1.24 in	5.1 to 6.0
2Bt2 20 to 30 in	clay	slow	1.18 to 1.48 in	5.1 to 6.0
3R 30 to 34 in	unweathered bedrock	impermeable		

Whalan

Extent: 45 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: loess over till over limestone residuum

Kw factor (surface layer) .37

Restrictive feature(s): lithic bedrock at 20 to 40 inches

Land capability, nonirrigated: 2e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: C

Representative soil profile	e: Texture	Permeability	Available water capacity	рН
A 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.6 to 7.3
Bt1 12 to 22 in	loam	moderate	1.74 to 1.94 in	5.1 to 6.5
2Bt2 22 to 24 in	silty clay	moderately slow	0.30 to 0.37 in	5.6 to 7.8
3R 24 to 34 in	weathered bedrock	rapid		



Fillmore County, Minnesota

Du--Dubuque and Whalan silt loams, 7 to 11 percent slopes, moderately eroded

Dubuque, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 48

Parent material: loess over limestone residuum Kw factor (surface layer) .43 Restrictive feature(s): lithic bedrock at 20 to 30 inches Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no Ponding: none Hydrologic group: D

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 3 in	silt loam	moderate	0.63 to 0.69 in	5.1 to 7.3
E 3 to 12 in	silt loam	moderate	1.56 to 1.73 in	5.1 to 6.0
Bt1 12 to 20 in	silty clay loam	slow	0.99 to 1.24 in	5.1 to 6.0
2Bt2 20 to 30 in	clay	slow	1.18 to 1.48 in	5.1 to 6.0
3R 30 to 34 in	unweathered bedrock	impermeable		

Whalan, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 48

Kw factor (surface layer) .37 Restrictive feature(s): lithic bedrock at 20 to 40 inches Land capability, nonirrigated: 3e

Hydric soil: no Flooding: none Ponding: none Hydrologic group: C

Parent material: loess over till over limestone residuum

Potential for frost action: moderate Drainage class: well drained

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.6 to 7.3
Bt1 12 to 22 in	loam	moderate	1.74 to 1.94 in	5.1 to 6.5
2Bt2 22 to 24 in	silty clay	moderately slow	0.30 to 0.37 in	5.6 to 7.8
3R 24 to 34 in	weathered bedrock	rapid		



Fillmore County, Minnesota

Dv--Dubuque and Whalan silt loams, 12 to 17 percent slopes, moderately eroded

Dubuque, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 48

Parent material: loess over limestone residuum

Kw factor (surface layer) .43

Restrictive feature(s): lithic bedrock at 20 to 30 inches

Land capability, nonirrigated: 6e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: D

Drainage class: well drained Potential for frost action: high

Representative soil profile	Texture	Permeability	Available water capacity	рН
Ap 0 to 3 in	silt loam	moderate	0.63 to 0.69 in	5.1 to 7.3
E 3 to 12 in	silt loam	moderate	1.56 to 1.73 in	5.1 to 6.0
Bt1 12 to 20 in	silty clay loam	slow	0.99 to 1.24 in	5.1 to 6.0
2Bt2 20 to 30 in	clay	slow	1.18 to 1.48 in	5.1 to 6.0
3R 30 to 34 in	unweathered bedrock	impermeable		

Whalan, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 48

Parent material: loess over till over limestone residuum

Kw factor (surface layer) .37

Restrictive feature(s): lithic bedrock at 20 to 40 inches

Land capability, nonirrigated: 4e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: C

Representative soil profile	: Texture	Permeability	Available water capacity	рН
A 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.6 to 7.3
Bt1 12 to 22 in	clay loam	moderate	1.74 to 1.94 in	5.1 to 6.5
2Bt2 22 to 24 in	clay loam	moderately slow	0.30 to 0.37 in	5.6 to 7.8
3R 24 to 34 in	weathered bedrock	rapid		



Fillmore County, Minnesota

Dx--Dubuque and Whalan silt loams, 18 to 45 percent slopes

Dubuque

Extent: 45 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 18 to 45 percent Wind erodibility index (WEI): 48

Restrictive feature(s): lithic bedrock at 20 to 30 inches

Land capability, nonirrigated: 7e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: D

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 3 in	silt loam	moderate	0.63 to 0.69 in	5.1 to 7.3
E 3 to 12 in	silt loam	moderate	1.56 to 1.73 in	5.1 to 6.0
Bt1 12 to 20 in	clay	slow	0.99 to 1.24 in	5.1 to 6.0
2Bt2 20 to 30 in	clay	slow	1.18 to 1.48 in	5.1 to 6.0
3R 30 to 34 in	unweathered bedrock	impermeable		

Whalan

Extent: 45 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 18 to 45 percent Wind erodibility index (WEI): 48

Parent material: loess over till over limestone residuum

Kw factor (surface layer) .37

Restrictive feature(s): lithic bedrock at 20 to 40 inches

Land capability, nonirrigated: 7e


Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: C

Representative soil profile	: Texture	Permeability	Available water capacity	рН
A 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.6 to 7.3
Bt1 12 to 22 in	clay loam	moderate	1.74 to 1.94 in	5.1 to 6.5
2Bt2 22 to 24 in	clay loam	moderately slow	0.30 to 0.37 in	5.6 to 7.8
3R 24 to 34 in	weathered bedrock	rapid		



Fillmore County, Minnesota

Ea--Escarpments

Escarpments

Extent: 90 percent of the unit

Soil loss tolerance (T factor): 5

Landform(s): hills Wind erodibility group (WEG): 2

Slope gradient: 12 to 50 percent Wind erodibility index (WEI): 134

Parent material: loess over limestone residuum and/or Kw factor (surface layer) .15

sandstone residuum

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative so	oil profile:	Texture	Permeability	Available water capacity	рН
A 0 1	to 8 in	loamy sand	rapid	0.71 to 0.94 in	5.1 to 7.3
B 8 f	to 48 in	loamy sand	rapid	1.61 to 2.81 in	4.5 to 6.5
C 48 1	to 60 in	sand	rapid	0.35 to 0.83 in	4.5 to 6.5

Fa--Fayette silt loam, 0 to 1 percent slopes

Fayette

Extent: 85 percent of the unit

Landform(s): loess hills

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 48
Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 1

Flooding: none

Hydric soil: no

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 14 in	silt loam	moderate	2.83 to 3.12 in	5.1 to 7.3
Bt 14 to 53 in	silt loam	moderate	7.02 to 7.80 in	4.5 to 6.5
C 53 to 60 in	silt loam	moderate	1.20 to 1.34 in	5.1 to 7.8



Fillmore County, Minnesota

Fb--Fayette silt loam, 2 to 6 percent slopes

Fayette

Extent: 85 percent of the unit

Landform(s): loess hills

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48
Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	рН
A 0 to 12 in	silt loam	moderate	2.36 to 2.60 in	5.1 to 7.3
Bt 12 to 53 in	silt loam	moderate	7.44 to 8.27 in	4.5 to 6.5
C 53 to 60 in	silt loam	moderate	1.20 to 1.34 in	5.1 to 7.8

Fd--Fayette silt loam, 7 to 11 percent slopes, moderately eroded

Fayette, moderately eroded

Extent: 85 percent of the unit

Soil loss tolerance (T factor): 5

Landform(s): loess hills

Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 48
Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil	profile:	Texture	Permeability	Available water capacity	рН
A 0 to	8 in	silt loam	moderate	1.42 to 1.57 in	5.1 to 7.3
Bt 8 to	40 in	silt loam	moderate	5.81 to 6.46 in	4.5 to 6.0
C 40 to	60 in	silt loam	moderate	3.54 to 3.94 in	5.1 to 7.8



A. . . : ! - b ! - . . . - t - . . .

Fillmore County, Minnesota

Ff--Fayette silt loam, 12 to 17 percent slopes, moderately eroded

Fayette, moderately eroded

Extent: 85 percent of the unit

Landform(s): loess hills

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 6

Slope gradient: 12 to 17 percent

Wind erodibility index (WEI): 48

Parent material: loess

Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative se	oil profile:	Texture	Permeability	Available water capacity	рН
A 0	to 8 in	silt loam	moderate	1.42 to 1.57 in	5.1 to 7.3
Bt 8	to 40 in	silt loam	moderate	5.81 to 6.46 in	4.5 to 6.0
C 40	to 60 in	silt loam	moderate	3.54 to 3.94 in	5.1 to 7.8

Fh--Fayette silt loam, 18 to 45 percent slopes

Fayette

Extent: 85 percent of the unit

Soil loss tolerance (T factor): 5

Landform(s): loess hills

Wind erodibility group (WEG): 6

Slope gradient: 18 to 45 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .37
Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 7e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
A	0 to 8 in	silt loam	moderate	1.57 to 1.73 in	5.1 to 7.3
Bt	8 to 40 in	silt loam	moderate	5.81 to 6.46 in	4.5 to 6.5
C 4	10 to 60 in	silt loam	moderate	3.54 to 3.94 in	5.1 to 7.8



Fillmore County, Minnesota

Fk--Fayette silt loam, terrace, 2 to 6 percent slopes

Fayette, terrace

Extent: 85 percent of the unit

Landform(s): terraces

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 48

Parent material: loess

Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none

Hydric soil: no
Ponding: none

Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative	soil profile:	Textu	ure	Permeability	Available water capacity	рН
Α	0 to 12 in	silt loam		moderate	2.36 to 2.60 in	5.1 to 7.3
Bt 12	2 to 53 in	silt loam		moderate	7.44 to 8.27 in	4.5 to 6.5
C 5	3 to 60 in	silt loam		moderate	1.20 to 1.34 in	5.1 to 7.8

Fm--Fayette silt loam, terrace, 7 to 17 percent slopes, moderately eroded

Fayette, terrace, moderately eroded

Extent: 85 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): terraces Wind erodibility group (WEG): 6
Slope gradient: 7 to 17 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile	e: Texture	Permeability	Available water capacity	рН
A 0 to 12 in	silt loam	moderate	2.13 to 2.36 in	5.1 to 7.3
Bt 12 to 53 in	silt loam	moderate	7.44 to 8.27 in	4.5 to 6.0
C 53 to 60 in	silt loam	moderate	1.20 to 1.34 in	5.1 to 7.8



Fillmore County, Minnesota

Fn--Floyd and Clyde silty clay loams, overwash, 0 to 3 percent slopes

Floyd, overwash

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): flats Wind erodibility group (WEG): 6

Slope gradient: 0 to 3 percent Wind erodibility index (WEI): 48

Parent material: silty alluvium over till Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2w

Flooding: none Hydric soil: yes

Ponding: none Hydrologic group: B/D

Drainage class: poorly drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	рН
A 0 to 16 in	silty clay loam	moderate	3.39 to 3.71 in	6.6 to 7.3
Bw 16 to 32 in	silty clay loam	moderate	2.83 to 3.15 in	6.1 to 7.3
2C 32 to 60 in	loam	moderate	4.75 to 5.31 in	6.1 to 7.8

Clyde, overwash

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): flats Wind erodibility group (WEG): 6

Slope gradient: 0 to 3 percent Wind erodibility index (WEI): 48

Parent material: silty alluvium over till Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2w

Flooding: none Hydric soil: yes
Ponding: none Hydrologic group: B/D

Drainage class: poorly drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	рН
A 0 to 16 in	silty clay loam	moderate	3.39 to 3.71 in	6.6 to 7.3
Bw 16 to 32 in	silt loam	moderate	2.83 to 3.15 in	6.1 to 7.3
2C 32 to 60 in	loam	moderate	4.75 to 5.31 in	6.1 to 7.8



A. . . : ! - b ! - . . . - t - . . .

Available water

Fillmore County, Minnesota

GP--Pits, gravel-Udipsamments complex

Pits, gravel

Extent: 45 to 55 percent of the unit Soil loss tolerance (T factor):

Landform(s): stream terraces, outwash plains, eskers, Wind erodibility group (WEG):

moraines

Slope gradient: 0 to 50 percent Wind erodibility index (WEI):

Parent material: Kw factor (surface layer)

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated:

Flooding: Hydric soil: no
Ponding: Hydrologic group:

Drainage class: Potential for frost action:

Representative soil profile:

Texture

Permeability

Available water capacity

PH

Udipsamments

Extent: 40 to 50 percent of the unit Soil loss tolerance (T factor):

Landform(s): stream terraces, outwash plains, eskers, Wind erodibility group (WEG):

moraines

Slope gradient: 0 to 25 percent Wind erodibility index (WEI):

Parent material: sandy and gravelly outwash Kw factor (surface layer)

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated:

Flooding: Hydric soil: no
Ponding: Hydrologic group:

Drainage class: excessively drained Potential for frost action:

Representative soil profile:

Texture

Permeability

Available water capacity

PH

Fillmore County, Minnesota

Ha--Hixton fine sandy loam, 2 to 11 percent slopes, moderately eroded

Hixton, moderately eroded

Extent: 85 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 3

Slope gradient: 2 to 11 percent Wind erodibility index (WEI): 86

Restrictive feature(s): paralithic bedrock at 20 to 40 inche

Land capability, nonirrigated: 3e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: C

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 14 in	fine sandy loam	moderate	1.84 to 2.13 in	5.1 to 7.3
Bt 14 to 32 in	sandy loam	moderate	2.13 to 3.37 in	5.1 to 6.0
C 32 to 45 in	sandy loam	moderate	1.04 to 2.34 in	5.1 to 6.0
2R 45 to 60 in	loamy fine sand	rapid	0.45 to 1.05 in	5.1 to 6.0



Fillmore County, Minnesota

Hb--Hixton fine sandy loam, 12 to 35 percent slopes, moderately eroded

Hixton, moderately eroded

Extent: 85 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 3

Slope gradient: 12 to 35 percent Wind erodibility index (WEI): 86

Restrictive feature(s): paralithic bedrock at 20 to 40 inche

Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: C

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 14 in	fine sandy loam	moderate	1.84 to 2.13 in	5.1 to 7.3
Bt 14 to 32 in	sandy loam	moderate	2.13 to 3.37 in	5.1 to 6.0
C 32 to 45 in	sandy loam	moderate	1.04 to 2.34 in	5.1 to 6.0
2R 45 to 60 in	loamy fine sand	rapid	0.45 to 1.05 in	5.1 to 6.0



Fillmore County, Minnesota

Ka--Kasson silt loam, 0 to 1 percent slopes

Kasson

Extent: 85 percent of the unit

Landform(s): till plains

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 48

Parent material: loess over till

Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 2s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: C

Drainage class: moderately well drained Potential for frost action: high

Representative soil profile	: Texture	Permeability	Available water capacity	рН
A 0 to 9 in	silt loam	moderate	1.99 to 2.17 in	5.6 to 6.5
Bt 9 to 24 in	silt loam	moderate	2.69 to 3.29 in	4.5 to 6.0
2C 24 to 60 in	loam	moderately slow	5.37 to 6.81 in	5.1 to 7.3

Kb--Kasson silt loam, 2 to 6 percent slopes

Kasson

Extent: 85 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains

Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 48

Parent material: loess over till Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 2e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: C

Drainage class: moderately well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 9 in	silt loam	moderate	1.99 to 2.17 in	5.6 to 6.5
Bt 9 to 24 in	silt loam	moderate	2.69 to 3.29 in	4.5 to 6.0
2C 24 to 60 in	loam	moderately slow	5.37 to 6.81 in	5.1 to 7.3



Fillmore County, Minnesota

Kc--Kato silty clay loam

Kato

Extent: 85 percent of the unit

Landform(s): outwash plains

Soil loss tolerance (T factor): 3

Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 48

Parent material: outwash

Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2w

Flooding: none Hydric soil: yes
Ponding: none Hydrologic group: B/D

Drainage class: poorly drained Potential for frost action: high

Representative soil profile.	Texture	Permeability	Available water capacity	рН
A 0 to 10 in	silty clay loam	moderate	1.77 to 2.36 in	6.1 to 7.8
Bg 10 to 35 in	silty clay loam	moderate	4.54 to 5.54 in	5.1 to 7.3
Ca 35 to 60 in	coarse sand	rapid	0.50 to 1.74 in	6.1 to 7.8



Fillmore County, Minnesota

Kd--Kenyon silt loam, 0 to 1 percent slopes

Kenyon

Extent: 85 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 48

Parent material: loess over till Kw factor (surface layer) .28

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 1

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: C

Drainage class: moderately well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 9 in	silt loam	moderate	1.81 to 1.99 in	5.1 to 7.3
A 9 to 14 in	silt loam	moderate	1.02 to 1.13 in	5.1 to 7.3
AB 14 to 19 in	silt loam	moderate	0.94 to 1.04 in	5.1 to 7.3
2Bw1 19 to 41 in	loam	moderate	3.75 to 4.19 in	5.1 to 7.3
2Bw2 41 to 55 in	loam	moderate	2.41 to 2.69 in	5.1 to 7.3
2BC1 55 to 71 in	loam	moderate	2.68 to 2.99 in	6.1 to 8.4
2BC2 71 to 79 in	loam	moderate	1.34 to 1.50 in	6.1 to 8.4

A. . . : ! - b ! - . . . - t - . . .

Fillmore County, Minnesota

Ke--Kenyon silt loam, 2 to 6 percent slopes

Kenyon

Extent: 85 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 48

Parent material: loess over till

Kw factor (surface layer) .28

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: C

Drainage class: moderately well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	silt loam	moderate	1.81 to 1.99 in	5.1 to 7.3
A 9 to 14 in	silt loam	moderate	1.02 to 1.13 in	5.1 to 7.3
AB 14 to 19 in	silt loam	moderate	0.94 to 1.04 in	5.1 to 7.3
2Bw1 19 to 41 in	loam	moderate	3.75 to 4.19 in	5.1 to 7.3
2Bw2 41 to 55 in	loam	moderate	2.41 to 2.69 in	5.1 to 7.3
2BC1 55 to 71 in	loam	moderate	2.68 to 2.99 in	6.1 to 8.4
2BC2 71 to 79 in	loam	moderate	1.34 to 1.50 in	6.1 to 8.4



A. . . : ! - b ! - . . . - t - . . .

Fillmore County, Minnesota

La--Lindstrom silt loam, 2 to 6 percent slopes

Lindstrom

Extent: 95 percent of the unit

Landform(s): valley sides

Solope gradient: 2 to 6 percent

Parent material: loamy colluvium

Restrictive feature(s): greater than 60 inches

Solope Solope Wind erodibility group (WEG): 5

Wind erodibility index (WEI): 56

Kw factor (surface layer) .32

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Α	0 to 9 in	silt loam	moderate	1.81 to 1.99 in	5.6 to 7.3
Bw	9 to 29 in	silt loam	moderate	4.42 to 5.22 in	5.6 to 7.3
C 2	29 to 60 in	silt loam	moderate	6.14 to 6.76 in	5.6 to 7.3

Lb--Lindstrom silt loam, 7 to 11 percent slopes, moderately eroded

Lindstrom, moderately eroded

Extent: 95 percent of the unit

Landform(s): valley sides

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 5

Slope gradient: 7 to 11 percent

Wind erodibility index (WEI): 56

Parent material: loamy colluvium

Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 9 in	silt loam	moderate	1.63 to 1.81 in	5.6 to 7.3
Bw 9 to 29 in	silt loam	moderate	4.42 to 5.22 in	5.6 to 7.3
C1 29 to 60 in	silt loam	moderate	6.14 to 6.76 in	5.6 to 7.3
C2 60 to 70 in	loam	moderate	1.74 to 1.94 in	6.6 to 7.8



Fillmore County, Minnesota

Lc--Lindstrom silt loam, 11 to 17 percent slopes, moderately eroded

Lindstrom, moderately eroded

Extent: 95 percent of the unit

Landform(s): valley sides

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 5

Slope gradient: 11 to 17 percent

Wind erodibility index (WEI): 56

Parent material: loamy colluvium

Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 9 in	silt loam	moderate	1.63 to 1.81 in	5.6 to 7.3
Bw 9 to 29 in	silt loam	moderate	4.42 to 5.22 in	5.6 to 7.3
C1 29 to 60 in	silt loam	moderate	6.14 to 6.76 in	5.6 to 7.3
C2 60 to 70 in	loam	moderate	1.74 to 1.94 in	6.6 to 7.8



Fillmore County, Minnesota

Ld--Lindstrom fine sandy loam, 18 to 45 percent slopes

Lindstrom

Extent: 95 percent of the unit Soil loss tolerance (T factor): 5
Landform(s): valley sides Wind erodibility group (WEG): 3

Slope gradient: 18 to 45 percent

Wind erodibility index (WEI): 86

Parent material: loamy colluvium


Kw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 10 in	fine sandy loam	moderately rapid	1.28 to 1.57 in	5.1 to 7.3
Bw 10 to 24 in	fine sandy loam	moderately rapid	1.70 to 1.98 in	4.5 to 6.5
C1 24 to 50 in	silt loam	moderate	5.20 to 5.72 in	4.5 to 6.5
C2 50 to 60 in	fine sandy loam	rapid	0.79 to 1.38 in	6.1 to 7.3



Fillmore County, Minnesota

M501A--Klossner muck, depressional, 0 to 1 percent slopes

Klossner, depressional

Extent: 70 to 90 percent of the unit

Landform(s): depressions on till plains

Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 134

Parent material: herbaceous organic material over loamy Kw factor (surface layer) .02

Soil loss tolerance (T factor): 1

Wind erodibility group (WEG): 2

deposits

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3w

Flooding: none Hydric soil: yes
Ponding: frequent Hydrologic group: B/D

Drainage class: very poorly drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Oap 0 to 10 in	muck	moderately rapid	3.44 to 4.72 in	5.6 to 6.0
Oa 10 to 26 in	muck	moderately rapid	5.65 to 7.75 in	5.6 to 6.0
2A1 26 to 36 in	mucky silty clay loam	moderate	2.17 to 2.56 in	6.6 to 7.3
2A2 36 to 48 in	silty clay loam	moderate	2.20 to 2.69 in	6.6 to 7.3
2Cg 48 to 80 in	loam	moderate	4.78 to 6.06 in	7.4 to 7.8

Fillmore County, Minnesota

M541C2--Copaston loam, 6 to 12 percent slopes, moderately eroded

Copaston, moderately eroded

Extent: 55 to 85 percent of the unit

Landform(s): hills

Slope gradient: 6 to 12 percent

Parent material: loamy sediments over limestone bedrock

Restrictive feature(s): lithic bedrock at 10 to 20 inches

Flooding: none Ponding: none

Drainage class: somewhat excessively drained

Soil loss tolerance (T factor): 1

Wind erodibility group (WEG): 6

Wind erodibility index (WEI): 48

Kw factor (surface layer) .32

w lactor (surface layer) .32

Land capability, nonirrigated: 6e

Hydric soil: no

Hydrologic group: D

Potential for frost action: moderate

Representative soil profile	e: Texture	Permeability	Available water capacity	рН
A 0 to 7 in	loam	moderate	1.42 to 1.56 in	5.6 to 7.3
AB 7 to 11 in	fine sandy loam	moderately rapid	0.59 to 0.75 in	5.6 to 7.3
Bw 11 to 18 in	sandy loam	moderately rapid	0.78 to 1.35 in	5.6 to 7.3
2R 18 to 60 in	unweathered bedrock	moderately slow		

Fillmore County, Minnesota

M541F--Copaston loam, 14 to 45 percent slopes

Copaston

Extent: 45 to 85 percent of the unit

Landform(s): valley sides

Slope gradient: 14 to 45 percent

Parent material: loamy sediments over limestone bedrock

Restrictive feature(s): lithic bedrock at 10 to 20 inches

Flooding: none Ponding: none

Drainage class: somewhat excessively drained

Soil loss tolerance (T factor): 1
Wind erodibility group (WEG): 6
Wind erodibility index (WEI): 48
Kw factor (surface layer) .32
Land capability, nonirrigated: 7e

Hydric soil: no Hydrologic group: D

Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 7 in	loam	moderate	1.42 to 1.56 in	5.6 to 7.3
AB 7 to 11 in	fine sandy loam	moderately rapid	0.59 to 0.75 in	5.6 to 7.3
Bw 11 to 18 in	sandy loam	moderately rapid	0.78 to 1.35 in	5.6 to 7.3
2R 18 to 60 in	unweathered bedrock	moderately slow		

Fillmore County, Minnesota

Ma--Marshan silty clay loam

Marshan

Extent: 90 percent of the unit

Landform(s): drainageways

Slope gradient: 0 to 1 percent

Parent material: silty alluvium over sandy outwash Restrictive feature(s): greater than 60 inches

Flooding: none Ponding: none

Drainage class: very poorly drained

Soil loss tolerance (T factor): 3
Wind erodibility group (WEG): 6
Wind erodibility index (WEI): 48
Kw factor (surface layer) .24
Land capability, nonirrigated: 3w

Hydric soil: yes

Hydrologic group: B/D

Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 14 in	silty clay loam	moderate	2.83 to 3.12 in	5.6 to 7.3
Bg1 14 to 23 in	silty clay loam	moderate	1.47 to 1.91 in	5.6 to 7.3
Bg2 23 to 30 in	loam	moderate	1.06 to 1.35 in	5.6 to 7.3
2Cg 30 to 60 in	sand	rapid	0.60 to 1.50 in	6.1 to 7.3

Fillmore County, Minnesota

Mc--Meridian fine sandy loam, 2 to 6 percent slopes

Meridian

Extent: 85 percent of the unit

Landform(s): terraces

Soil loss tolerance (T factor): 3

Wind erodibility group (WEG): 3

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 86

Parent material: sandy and silty alluvium

Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	pН
A 0 to 10 in	fine sandy loam	moderate	1.28 to 1.77 in	6.1 to 7.8
Bt1 10 to 15 in	loam	moderate	0.82 to 0.97 in	5.1 to 6.5
2Bt2 15 to 29 in	sandy loam	moderately rapid	1.28 to 1.98 in	5.1 to 6.5
2C 29 to 60 in	sand	rapid	1.54 to 3.07 in	5.1 to 6.5

Md--Mixed alluvial land, 0 to 6 percent slopes

Mixed alluvial land, frequently flooded, ponded

Extent: 95 percent of the unit

Landform(s): flood plains

Soil loss tolerance (T factor):

Wind erodibility group (WEG):

Slope gradient: 0 to 6 percent

Wind erodibility index (WEI):

Parent material: sandy and silty alluvium

Kw factor (surface layer)

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated:

Flooding: frequent

Hydric soil: yes

Ponding: frequent

Hydrologic group:

Drainage class: poorly drained Potential for frost action:


Representative soil profile:

Texture

Permeability

Available water capacity

pH



I Available water

Fillmore County, Minnesota

Me--Mixed alluvial land, 7 to 17 percent slopes

Mixed alluvial land, very rarely flooded

Extent: 95 percent of the unit

Landform(s): flood plains

Soil loss tolerance (T factor):

Wind erodibility group (WEG):

Slope gradient: 7 to 17 percent Wind erodibility index (WEI):

Parent material: sandy and silty alluvium Kw factor (surface layer)

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated:

Flooding: very rareHydric soil: noPonding: noneHydrologic group:

Drainage class: well drained Potential for frost action:

Representative soil profile:

Texture

Permeability

Available water capacity

PH

N502B--Nordness silt loam, 2 to 6 percent slopes

Nordness

Extent: 50 to 85 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: loamy or silty material over clayey residuum Kw factor (surface layer) .37 over limestone or dolomite

Restrictive feature(s): lithic bedrock at 8 to 20 inches Land capability, nonirrigated: 6s

Flooding: noneHydric soil: noPonding: noneHydrologic group: D

Drainage class: well drained Potential for frost action: moderate

Representative soil profile.		Texture	Permeability	Available water capacity	рН
A 0 to 4 in	silt loam		moderate	0.79 to 0.87 in	5.6 to 7.3
BE 4 to 7 in	silt loam		moderate	0.63 to 0.69 in	5.6 to 7.3
Bt1 7 to 13 in	silt loam		moderate	1.18 to 1.30 in	5.6 to 7.3
2Bt2 13 to 16 in	clay		slow	0.38 to 0.47 in	6.6 to 7.3
3R 16 to 80 in	bedrock		moderately slow		



This report shows only the major soils in each map unit

Fillmore County, Minnesota

N502C--Nordness silt loam, 6 to 12 percent slopes

Nordness

Extent: 50 to 85 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 6 to 12 percent Wind erodibility index (WEI): 48

Parent material: loamy or silty material over clayey residuum Kw factor (surface layer) .37 over limestone or dolomite

Restrictive feature(s): lithic bedrock at 8 to 20 inches

Land capability, nonirrigated: 6s

Flooding: none

Hydric soil: no
Ponding: none

Hydrologic group: D

Representativ	e soil profile:		Texture	Permeability	Available water capacity	рН
A	0 to 4 in	silt loam		moderate	0.79 to 0.87 in	5.6 to 7.3
BE	4 to 7 in	silt loam		moderate	0.63 to 0.69 in	5.6 to 7.3
Bt1	7 to 13 in	silt loam		moderate	1.18 to 1.30 in	5.6 to 7.3
2Bt2	13 to 16 in	clay		slow	0.38 to 0.47 in	6.6 to 7.3
3R	16 to 80 in	bedrock		moderately slow		



Fillmore County, Minnesota

N509F--Bellechester-Etter complex, 18 to 45 percent slopes

Bellechester

Extent: 30 to 70 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): valley sides Wind erodibility group (WEG): 3

Slope gradient: 18 to 45 percent Wind erodibility index (WEI): 86

Restrictive feature(s): paralithic bedrock at 36 to 71 inche

Land capability, nonirrigated: 7s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Drainage class: excessively drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 12 in	sandy loam	moderately rapid	1.42 to 1.65 in	6.1 to 7.8
Bw 12 to 19 in	loamy sand	rapid	0.71 to 0.99 in	5.6 to 7.8
C 19 to 36 in	fine sand	rapid	0.68 to 1.69 in	5.6 to 7.8
Cr 36 to 80 in	weathered bedrock	moderate		

Etter

Extent: 15 to 50 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): valley sides Wind erodibility group (WEG): 3

Slope gradient: 18 to 35 percent Wind erodibility index (WEI): 86

Parent material: mixed loess and erosional sediments and the Kw factor (surface layer) .24 underlying sandstone residuum

Restrictive feature(s): paralithic bedrock at 35 to 80 inche

Land capability, nonirrigated: 7e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: C

Drainage class: well drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	capacity	рН
A 0 to 16 in	sandy loam	moderate	2.58 to 2.91 in	5.6 to 7.3
Bw 16 to 31 in	sandy loam	moderate	1.80 to 2.84 in	4.5 to 7.3
2C 31 to 35 in	fine sand	rapid	0.20 to 0.39 in	4.5 to 8.4
2Cr 35 to 80 in	fine sand	moderate	2.24 to 4.49 in	4.5 to 8.4



Available water

Fillmore County, Minnesota

N510E--Sylvester-Downs complex, 20 to 45 percent slopes

Sylvester

Extent: 40 to 85 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): valley sides Wind erodibility group (WEG): 5

Slope gradient: 20 to 45 percent Wind erodibility index (WEI): 56

Restrictive feature(s): paralithic bedrock at 24 to 40 inche

Land capability, nonirrigated: 7e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: C

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	pН
A 0 to 15 in	silt loam	moderate	3.29 to 3.59 in	5.6 to 7.3
Bt 15 to 30 in	silty clay loam	moderate	2.99 to 3.29 in	5.1 to 6.5
2BC 30 to 32 in	loamy sand	moderately rapid	0.16 to 0.28 in	5.1 to 6.5
2Cr 32 to 60 in	weathered bedrock	moderate		

Downs

Extent: 15 to 55 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): valley sides Wind erodibility group (WEG): 5

Slope gradient: 20 to 30 percent Wind erodibility index (WEI): 56

Parent material: loess Kw factor (surface layer) .37
Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative s	oil profile:	Texture	Permeability	Available water capacity	рН
A,AB 0	to 9 in	silt loam	moderate	1.99 to 2.17 in	5.6 to 7.3
Bt 9	to 52 in	silt loam	moderate	8.58 to 9.44 in	5.1 to 6.5
BC 52	to 80 in	silt loam	moderate	5.59 to 6.15 in	5.1 to 7.8



Fillmore County, Minnesota

N531B--Downs-Nasset complex, sinkhole karst, 2 to 6 percent slopes

Downs, sinkhole karst

Extent: 65 to 90 percent of the unit

Soil loss tolerance (T factor): 5

Landform(s): hills Wind erodibility group (WEG): 5

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 56

Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 8 in	silt loam	moderate	1.73 to 1.89 in	5.6 to 7.3
E,BE 8 to 17 in	silt loam	moderate	1.81 to 1.99 in	5.6 to 7.3
Bt 17 to 39 in	silty clay loam	moderate	4.41 to 4.85 in	5.1 to 6.5
BC,C 39 to 60 in	silt loam	moderate	4.17 to 4.59 in	5.1 to 7.8

Nasset, sinkhole karst

Extent: 5 to 20 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): hills Wind erodibility group (WEG): 5

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 56


Restrictive feature(s): lithic bedrock at 40 to 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: C

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 6 in	silt loam	moderate	1.30 to 1.42 in	5.6 to 7.3
BE 6 to 12 in	silt loam	moderate	1.18 to 1.30 in	5.6 to 7.3
Bt 12 to 37 in	silty clay loam	moderate	5.04 to 5.54 in	5.1 to 6.5
2Bt 37 to 44 in	clay	slow	0.57 to 0.85 in	6.6 to 7.3
3R 44 to 60 in	weathered bedrock	moderately slow		



This report shows only the major soils in each map unit

Fillmore County, Minnesota

N532C2--Fayette-Pepin complex, sinkhole karst, 6 to 12 percent slopes, moderately eroded

Fayette, sinkhole karst, moderately eroded

Extent: 40 to 90 percent of the unit

Landform(s): hills

Slope gradient: 6 to 12 percent

Parent material: loess

Restrictive feature(s): greater than 60 inches

Flooding: none Ponding: none

Drainage class: well drained

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 5

Wind erodibility index (WEI): 56

Kw factor (surface layer) .43

Land capability, nonirrigated: 3e

Hydric soil: no

Hydrologic group: B

Potential for frost action: high

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Ap	0 to 9 in	silt loam	moderate	1.99 to 2.17 in	5.6 to 7.3
Bt	9 to 50 in	silty clay loam	moderate	8.19 to 9.01 in	5.1 to 6.5
BC 50	0 to 80 in	silt loam	moderate	5.98 to 6.58 in	5.1 to 7.8

Pepin, sinkhole karst, moderately eroded

Extent: 5 to 30 percent of the unit

Landform(s): hills

Slope gradient: 6 to 12 percent

Parent material: loess over residuum over limestone bedrock

Restrictive feature(s): lithic bedrock at 40 to 80 inches

Flooding: none Ponding: none

Drainage class: well drained

Soil loss tolerance (T factor): 4

Wind erodibility group (WEG): 5

Wind erodibility index (WEI): 56
Kw factor (surface layer) .49


Land capability, nonirrigated: 3e

Hydric soil: no

Hydrologic group: B

Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	silt loam	moderate	1.99 to 2.17 in	5.6 to 7.3
Bt 9 to 48 in	silt loam	moderate	7.80 to 8.57 in	5.1 to 6.5
2Bt 48 to 58 in	clay	slow	0.79 to 1.57 in	5.6 to 7.3
3Bt 58 to 66 in	very flaggy loam	moderate	0.50 to 1.32 in	5.6 to 7.8
3R 66 to 80 in	weathered bedrock	rapid		



Fillmore County, Minnesota

N533D2--Fayette-Pepin-Dubuque complex, sinkhole karst, 12 to 18 percent slopes, moderately eroded

Fayette, sinkhole karst, moderately eroded

Extent: 15 to 50 percent of the unit

Landform(s): hills

Slope gradient: 12 to 18 percent

Parent material: loess

Restrictive feature(s): greater than 60 inches

Flooding: none Ponding: none

Drainage class: well drained

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 5 Wind erodibility index (WEI): 56

Kw factor (surface layer) .43

Land capability, nonirrigated: 4e

Hydric soil: no

Hydrologic group: B

Potential for frost action: high

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Ap	0 to 9 in	silt loam	moderate	1.99 to 2.17 in	5.6 to 7.3
Bt	9 to 50 in	silty clay loam	moderate	8.19 to 9.01 in	5.1 to 6.5
BC 50	0 to 80 in	silt loam	moderate	5.98 to 6.58 in	5.1 to 7.8

Pepin, sinkhole karst, moderately eroded

Extent: 15 to 40 percent of the unit

Landform(s): hills

Slope gradient: 12 to 18 percent

Parent material: loess over residuum over limestone bedrock

Restrictive feature(s): lithic bedrock at 40 to 80 inches

Flooding: none

Ponding: none

Drainage class: well drained

Soil loss tolerance (T factor): 4

Wind erodibility group (WEG): 5

Wind erodibility index (WEI): 56

Kw factor (surface layer) .49


Land capability, nonirrigated: 4e

Hydric soil: no

Hydrologic group: B

Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	silt loam	moderate	1.99 to 2.17 in	5.6 to 7.3
Bt 9 to 48 in	silt loam	moderate	7.80 to 8.57 in	5.1 to 6.5
2Bt 48 to 58 in	clay	slow	0.79 to 1.57 in	5.6 to 7.3
3Bt 58 to 66 in	very flaggy loam	moderate	0.50 to 1.32 in	5.6 to 7.8
3R 66 to 80 in	weathered bedrock	rapid		



Fillmore County, Minnesota

N533D2--Fayette-Pepin-Dubuque complex, sinkhole karst, 12 to 18 percent slopes, moderately eroded

Dubuque, sinkhole karst, moderately eroded

Extent: 15 to 30 percent of the unit

Landform(s): -- error in exists on -
Slope gradient: 12 to 18 percent

Parent material: loess over clayey residuum over limestone

Soil loss tolerance (T factor): 2

Wind erodibility group (WEG): 5

Wind erodibility index (WEI): 56

Kw factor (surface layer) .43

bedrock

Restrictive feature(s): lithic bedrock at 20 to 40 inches

Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: C

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 8 in	silt loam	moderate	1.73 to 1.89 in	5.6 to 7.3
Bt 8 to 29 in	silty clay loam	moderate	4.25 to 4.68 in	5.6 to 7.3
2Bt 29 to 30 in	clay	slow	0.06 to 0.09 in	6.1 to 7.3
3R 30 to 80 in	weathered bedrock	rapid		



Fillmore County, Minnesota

N580G--Brodale, very flaggy-Bellechester-Rock outcrop complex, 45 to 90 percent slopes

Brodale, very flaggy

Extent: 20 to 70 percent of the unit

Landform(s): valley sides Wind erodibility group (WEG): 6

Slope gradient: 45 to 90 percent Wind erodibility index (WEI): 48

Soil loss tolerance (T factor): 2

Parent material: loamy-skeletal colluvium Kw factor (surface layer) .10

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7s

Flooding: none

Hydric soil: no

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: excessively drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 12 in	very flaggy loam	moderate	0.83 to 1.77 in	6.6 to 8.4
C 12 to 60 in	very flaggy loam	moderately rapid	1.92 to 7.20 in	7.4 to 8.4

Bellechester

Extent: 15 to 30 percent of the unit Soil loss tolerance (T factor): 4

Landform(s): valley sides Wind erodibility group (WEG): 1

Slope gradient: 45 to 90 percent Wind erodibility index (WEI): 220

Parent material: sandy colluvium and/or residuum Kw factor (surface layer) .05

Restrictive feature(s): paralithic bedrock at 40 to 60 inche

Land capability, nonirrigated: 7s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representativ	e soil profile:	Texture	Permeability	Available water capacity	рН
A	0 to 16 in	sand	rapid	0.81 to 1.29 in	6.1 to 8.4
Bw1,Bw2,BC	16 to 42 in	sand	rapid	0.78 to 2.60 in	6.6 to 8.4
Cr	42 to 60 in	weathered bedrock	moderate		



Fillmore County, Minnesota

N580G--Brodale, very flaggy-Bellechester-Rock outcrop complex, 45 to 90 percent slopes

Rock outcrop

Extent: 5 to 15 percent of the unit

Soil loss tolerance (T factor):

Landform(s): valley sides Wind erodibility group (WEG): Slope gradient: Wind erodibility index (WEI):

Parent material: Kw factor (surface layer)

Restrictive feature(s): lithic bedrock

Land capability, nonirrigated: 8

Flooding: none Hydric soil: no
Ponding: none Hydrologic group:

Drainage class: Potential for frost action:

Representative soil profile:

Texture

Permeability

Available water capacity

pH

Fillmore County, Minnesota

N638G--Brodale, flaggy-Bellechester complex, 30 to 70 percent slopes

Brodale, flaggy

Extent: 20 to 75 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): valley sides Wind erodibility group (WEG): 5

Slope gradient: 30 to 70 percent Wind erodibility index (WEI): 56

Parent material: loamy colluvium Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Drainage class: excessively drained Potential for frost action: moderate

Representative soil p	orofile:	Texture	Permeability	capacity	рН
A 0 to 1	12 in channery lo	oam	moderate	1.54 to 2.01 in	6.6 to 8.4
C 12 to 6	60 in very flaggy	loam	moderately rapid	3.36 to 7.20 in	7.4 to 8.4

Bellechester

Extent: 15 to 30 percent of the unit Soil loss tolerance (T factor): 4

Landform(s): valley sides Wind erodibility group (WEG): 2

Slope gradient: 30 to 70 percent Wind erodibility index (WEI): 134

Parent material: sandy colluvium and/or residuum

Kw factor (surface layer) .10

Restrictive feature(s): paralithic bedrock at 40 to 60 inche

Land capability, nonirrigated: 7s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Α	0 to 16 in	loamy sand	rapid	1.61 to 2.26 in	6.1 to 7.8
Bw,BC 1	16 to 42 in	sand	rapid	1.04 to 2.08 in	6.6 to 8.4
Cr 4	12 to 60 in	weathered bedrock	moderate		



Available water

Fillmore County, Minnesota

N639F--Frontenac-Lacrescent complex, 20 to 45 percent slopes

Frontenac

Extent: 20 to 85 percent of the unit Soil loss tolerance (T factor): 4

Landform(s): valley sides Wind erodibility group (WEG): 6

Slope gradient: 20 to 45 percent Wind erodibility index (WEI): 48

Parent material: loamy sediments over loamy-skeletal Kw factor (surface layer) .28 colluvium

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7e

Flooding: none

Hydric soil: no

Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile	Texture	Permeability	Available water capacity	рН
A,AB 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.6 to 7.3
Bw 12 to 30 in	silt loam	moderate	3.08 to 3.98 in	5.6 to 7.3
2C 30 to 80 in	very channery loam	moderately rapid	3 00 to 8 00 in	6.6 to 7.8

Lacrescent

Extent: 15 to 60 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): valley sides Wind erodibility group (WEG): 6

Slope gradient: 20 to 45 percent Wind erodibility index (WEI): 48

Parent material: silty and loamy sediments over loamyskeletal colluvium

Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	6.1 to 7.3
AB 10 to 17 in	channery silt loam	moderate	1.20 to 1.35 in	6.1 to 7.3
2Bw 17 to 28 in	very channery silt loam	moderately rapid	0.77 to 1.76 in	6.1 to 7.3
2C 28 to 60 in	very channery silt loam	moderately rapid	2.23 to 5.10 in	7.4 to 7.8



Fillmore County, Minnesota

N639G--Frontenac-Lacrescent complex, 30 to 70 percent slopes

Frontenac

Extent: 20 to 85 percent of the unit Soil loss tolerance (T factor): 4

Landform(s): valley sides Wind erodibility group (WEG): 6

Slope gradient: 30 to 70 percent Wind erodibility index (WEI): 48

Parent material: loamy sediments over loamy-skeletal Kw factor (surface layer) .28 colluvium

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A,AB 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.6 to 7.3
Bw 12 to 30 in	silt loam	moderate	3.08 to 3.98 in	5.6 to 7.3
2C 30 to 80 in	very channery loam	moderately rapid	3.00 to 8.00 in	6.6 to 7.8

Lacrescent

Extent: 15 to 60 percent of the unit Soil loss tolerance (T factor): 3

Landform(s): valley sides Wind erodibility group (WEG): 6

Slope gradient: 30 to 70 percent Wind erodibility index (WEI): 48

Parent material: silty and loamy sediments over loamy
Kw factor (surface layer) .37

skeletal colluvium

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 7e


Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
A 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	6.1 to 7.3
AB 10 to 17 in	channery silt loam	moderate	1.20 to 1.35 in	6.1 to 7.3
2Bw 17 to 28 in	very channery silt loam	moderately rapid	0.77 to 1.76 in	6.1 to 7.3
2C 28 to 60 in	very channery silt loam	moderately rapid	2.23 to 5.10 in	7.4 to 7.8



Fillmore County, Minnesota

N640G--Lacrescent, flaggy-Frontenac-Rock outcrop complex, 45 to 90 percent slopes

Lacrescent, flaggy

Extent: 20 to 80 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): valley sides Wind erodibility group (WEG): 7

Slope gradient: 45 to 90 percent Wind erodibility index (WEI): 38

Parent material: silty and loamy sediments over loamyskeletal colluvium

Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7e

Flooding: none

Hydric soil: no

Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile.	Texture	Permeability	Available water capacity	рН
A,AB 0 to 17 in	flaggy silt loam	moderate	3.05 to 3.72 in	6.6 to 7.3
2Bw 17 to 28 in	very channery silt loam	moderately rapid	0.88 to 1.65 in	6.1 to 7.3
2C 28 to 60 in	very channery silt loam	moderately rapid	2.23 to 5.10 in	7.4 to 7.8

Frontenac

Extent: 15 to 45 percent of the unit Soil loss tolerance (T factor): 4

Landform(s): valley sides Wind erodibility group (WEG): 6

Slope gradient: 45 to 90 percent Wind erodibility index (WEI): 48

Parent material: loamy sediments over loamy-skeletal Kw factor (surface layer) .28

colluvium

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 7e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	рН
A,AB 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.6 to 7.3
Bw 12 to 30 in	silt loam	moderate	3.08 to 3.98 in	5.6 to 7.3
2C 30 to 80 in	very channery loam	moderately rapid	3.00 to 8.00 in	6.6 to 7.8



Available water

Fillmore County, Minnesota

N640G--Lacrescent, flaggy-Frontenac-Rock outcrop complex, 45 to 90 percent slopes

Rock outcrop

Extent: 5 to 15 percent of the unit Soil loss tolerance (T factor):

Landform(s): valley sides Wind erodibility group (WEG):

Slope gradient: Wind erodibility index (WEI):
Parent material: Kw factor (surface layer)

Restrictive feature(s): lithic bedrock

Land capability, nonirrigated: 8

Flooding: none

Hydric soil: no

Hydrologic group:

Drainage class: Potential for frost action:

Representative soil profile:

Texture

Permeability

Available water capacity

PH

N641F--Brodale channery loam, 20 to 45 percent slopes

Brodale, flaggy

Extent: 55 to 85 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): valley sides Wind erodibility group (WEG): 5

Slope gradient: 20 to 45 percent

Wind erodibility index (WEI): 56

Parent material: loamy-skeletal colluvium

Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 7s

Flooding: none

Hydric soil: no
Ponding: none

Hydrologic group: B

Drainage class: excessively drained Potential for frost action: moderate

Representative soil profile:

A -- 0 to 12 in flaggy loam

Texture

Permeability


Available water capacity

pH

moderate

1.54 to 2.01 in 6.6 to 8.4

A -- 0 to 12 in flaggy loam moderate 1.54 to 2.01 in 6.6 to 8.4 C -- 12 to 60 in very flaggy loam moderately rapid 3.36 to 7.20 in 7.4 to 8.4



Fillmore County, Minnesota

Pa--Plainfield and Sparta loamy fine sands, 2 to 6 percent slopes

Plainfield

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): terraces Wind erodibility group (WEG): 2

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 134

Parent material: eolian deposits Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Α	0 to 8 in	loamy fine sand	rapid	0.71 to 0.94 in	5.1 to 7.3
Bw	8 to 48 in	loamy sand	rapid	1.61 to 2.81 in	4.5 to 6.5
C 4	8 to 60 in	fine sand	rapid	0.35 to 0.83 in	4.5 to 6.5

Sparta

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): terraces Wind erodibility group (WEG): 2

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 134

Parent material: eolian deposits Kw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative soil pr	rofile:	Texture Permea	ability capacity	рН
A 0 to 15	5 in loamy fine sa	and moderate	ely rapid 1.35 to 1.80 in	5.1 to 7.3
Bw 15 to 34	4 in loamy fine sa	and rap	oid 0.94 to 2.08 in	5.1 to 7.3
E&Bt 34 to 60	0 in sand	rap	oid 1.04 to 1.82 in	5.1 to 7.8



Available water

Fillmore County, Minnesota

Pb--Plainfield and Sparta loamy fine sands, 7 to 11 percent slopes

Plainfield

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): terraces Wind erodibility group (WEG): 2

Slope gradient: 7 to 11 percent

Wind erodibility index (WEI): 134

Parent material: eolian deposits

Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 6s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Α	0 to 8 in	loamy fine sand	rapid	0.71 to 0.94 in	5.1 to 7.3
Bw	8 to 48 in	loamy sand	rapid	1.61 to 2.81 in	4.5 to 6.5
C 4	8 to 60 in	fine sand	rapid	0.35 to 0.83 in	4.5 to 6.5

Sparta

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): terraces Wind erodibility group (WEG): 2

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 134

Parent material: eolian deposits Kw factor (surface layer) .20

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 6s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: excessively drained Potential for frost action: low

Representative	e soil profile:	Texture	Permeability	Available water capacity	рН
A	0 to 15 in	loamy fine sand	moderately rapid	1.35 to 1.80 in	5.1 to 7.3
Bw	15 to 34 in	loamy fine sand	rapid	0.94 to 2.08 in	5.1 to 7.3
E&Bt	34 to 60 in	sand	rapid	1.04 to 1.82 in	5.1 to 7.8



Fillmore County, Minnesota

Ra--Racine and Ostrander silt loams, 0 to 1 percent slopes

Racine

Extent: 40 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 48

Parent material: loess over till Kw factor (surface layer) .28

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 1

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.1 to 7.3
Bt1 12 to 18 in	silt loam	moderate	1.26 to 1.39 in	4.5 to 6.0
2Bt2 18 to 46 in	clay loam	moderate	4.19 to 5.31 in	4.5 to 6.0
2C 46 to 60 in	clay loam	moderately slow	1.38 to 2.07 in	6.6 to 8.4

Ostrander

Extent: 40 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 48

Parent material: loess over till

Kw factor (surface layer) .28

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 1

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 16 in	silt loam	moderate	3.23 to 3.87 in	5.6 to 7.3
Bt1 16 to 20 in	silt loam	moderate	0.67 to 0.79 in	5.1 to 7.3
2Bt2 20 to 50 in	loam	moderate	5.09 to 5.69 in	5.1 to 7.3
3C 50 to 60 in	loam	moderate	1.67 to 1.87 in	6.6 to 7.8



Fillmore County, Minnesota

Rb--Racine and Ostrander silt loams, 2 to 6 percent slopes

Racine

Extent: 40 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains

Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 48

Parent material: loess over till

Kw factor (surface layer) .28

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.1 to 7.3
Bt1 12 to 18 in	silt loam	moderate	1.26 to 1.39 in	4.5 to 6.0
2Bt2 18 to 46 in	clay loam	moderate	4.19 to 5.31 in	4.5 to 6.0
2C 46 to 60 in	clay loam	moderately slow	1.38 to 2.07 in	6.6 to 8.4

Ostrander

Extent: 40 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 48

Parent material: loess over till

Kw factor (surface layer) .28


Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 16 in	silt loam	moderate	3.23 to 3.87 in	5.6 to 7.3
Bt1 16 to 20 in	silt loam	moderate	0.67 to 0.79 in	5.1 to 7.3
2Bt2 20 to 50 in	loam	moderate	5.09 to 5.69 in	5.1 to 7.3
3C 50 to 60 in	loam	moderate	1.67 to 1.87 in	6.6 to 7.8



A. allahla ...atau

Fillmore County, Minnesota

Rd--Racine and Ostrander silt loams, 7 to 11 percent slopes, moderately eroded

Racine, moderately eroded

Extent: 40 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 48

Parent material: loess over till Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.1 to 7.3
Bt1 12 to 18 in	silt loam	moderate	1.26 to 1.39 in	4.5 to 6.0
2Bt2 18 to 46 in	clay loam	moderate	4.19 to 5.31 in	4.5 to 6.0
2C 46 to 60 in	clay loam	moderately slow	1.38 to 2.07 in	6.6 to 8.4

Ostrander, moderately eroded

Extent: 40 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 48

Parent material: loess over till Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 16 in	silt loam	moderate	3.23 to 3.87 in	5.6 to 7.3
Bt1 16 to 20 in	silt loam	moderate	0.67 to 0.79 in	5.1 to 7.3
2Bt2 20 to 50 in	loam	moderate	5.09 to 5.69 in	5.1 to 7.3
3C 50 to 60 in	loam	moderate	1.67 to 1.87 in	6.6 to 7.8



Fillmore County, Minnesota

Re--Racine and Ostrander loams, 12 to 17 percent slopes, moderately eroded

Racine, moderately eroded

Extent: 40 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains

Wind erodibility group (WEG): 6

Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 48

Parent material: loess over till Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 12 in	loam	moderate	2.60 to 2.83 in	5.1 to 7.3
Bt1 12 to 18 in	silt loam	moderate	1.26 to 1.39 in	4.5 to 6.0
2Bt2 18 to 46 in	clay loam	moderate	4.19 to 5.31 in	4.5 to 6.0
2C 46 to 60 in	clay loam	moderately slow	1.38 to 2.07 in	6.6 to 8.4

Ostrander, moderately eroded

Extent: 40 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 48

Parent material: loess over till Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 16 in	loam	moderate	3.55 to 3.87 in	5.1 to 7.3
Bt1 16 to 20 in	silt loam	moderate	0.67 to 0.79 in	5.1 to 7.3
2Bt2 20 to 50 in	loam	moderate	5.09 to 5.69 in	5.1 to 7.3
3C 50 to 60 in	loam	moderate	1.67 to 1.87 in	6.6 to 7.8



I Amellahla matau I

Fillmore County, Minnesota

Rf--Renova silt loam, 0 to 1 percent slopes

Renova

Extent: 90 percent of the unit

Soil loss tolerance (T factor): 5

Landform(s): till plains

Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 48

Parent material: loess over till

Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 1

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile	: Texture	Permeability	Available water capacity	рН
Ap 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	5.6 to 6.5
Bt1 10 to 24 in	silty clay loam	moderate	2.83 to 3.12 in	4.5 to 6.0
2Bt2 24 to 52 in	clay loam	moderate	4.75 to 5.31 in	4.5 to 7.3
2C 52 to 60 in	loam	moderately slow	0.79 to 1.18 in	7.4 to 8.4

Fillmore County, Minnesota

Rg--Renova silt loam, 2 to 6 percent slopes

Renova

Extent: 90 percent of the unit

Soil loss tolerance (T factor): 5

Landform(s): till plains

Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 48

Parent material: loess over till

Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	5.6 to 6.5
Bt1 10 to 24 in	silty clay loam	moderate	2.83 to 3.12 in	4.5 to 6.0
2Bt2 24 to 52 in	clay loam	moderate	4.75 to 5.31 in	4.5 to 7.3
2C 52 to 60 in	loam	moderately slow	0.79 to 1.18 in	7.4 to 8.4



Fillmore County, Minnesota

Rk--Renova silt loam, 7 to 11 percent slopes, moderately eroded

Renova, moderately eroded

Extent: 90 percent of the unit

Soil loss tolerance (T factor): 5

Landform(s): till plains

Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent

Parent material: loess over till

Restrictive feature(s): greater than 60 inches

Wind erodibility index (WEI): 48

Kw factor (surface layer) .37

Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil pro	file: Texture	Permeability	Available water capacity	рН
Ap 0 to 10 ii	n silt loam	moderate	2.17 to 2.36 in	5.6 to 6.5
Bt1 10 to 24 in	n silty clay loam	moderate	2.83 to 3.12 in	4.5 to 6.0
2Bt2 24 to 52 ii	n clay loam	moderate	4.75 to 5.31 in	4.5 to 7.3
2C 52 to 60 ii	n loam	moderately slow	0.79 to 1.18 in	7.4 to 8.4



Fillmore County, Minnesota

RI--Renova loam, 12 to 17 percent slopes, moderately eroded

Renova, moderately eroded

Extent: 90 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plainsWind erodibility group (WEG): 6Slope gradient: 12 to 17 percentWind erodibility index (WEI): 48Parent material: loess over tillKw factor (surface layer) .37Restrictive feature(s): greater than 60 inchesLand capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 10 in	loam	moderate	2.17 to 2.36 in	5.6 to 6.5
Bt1 10 to 24 in	silty clay loam	moderate	2.83 to 3.12 in	4.5 to 6.0
2Bt2 24 to 52 in	clay loam	moderate	4.75 to 5.31 in	4.5 to 7.3
2C 52 to 60 in	loam	moderately slow	0.79 to 1.18 in	7.4 to 8.4



Fillmore County, Minnesota

Rm--Rockton and Dodgeville silt loams, shallow, 2 to 6 percent slopes

Dodgeville

Extent: 45 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 5

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 56

Parent material: loamy sediments over residuum over Kw factor (surface layer) .32

Restrictive feature(s): lithic bedrock at 10 to 20 inches

Land capability, nonirrigated: 6e

Flooding: none

Hydric soil: no

Hydrologic group: D

Drainage class: well drained Potential for frost action: low

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Ap (0 to 7 in	silt loam	moderate	1.13 to 1.28 in	6.6 to 8.4
Bt	7 to 16 in	silt loam	moderate	1.36 to 1.99 in	6.1 to 8.4
2R 10	6 to 60 in	bedrock	moderately rapid		7.9 to 8.4

Rockton

Extent: 45 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: loamy sediments over residuum over Kw factor (surface layer) .32

limestone bedrock

limestone bedrock

Restrictive feature(s): lithic bedrock at 10 to 20 inches

Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: D

Representative soil profile:		Texture	Permeability	Available water capacity	рН
Ap 0	to 7 in	silt loam	moderate	1.06 to 1.63 in	6.1 to 8.4
Bt 7	to 18 in	silt loam	moderate	1.65 to 2.43 in	6.1 to 8.4
2R 18	to 60 in	unweathered bedrock	moderately slow		



Fillmore County, Minnesota

Ro--Rockton and Dodgeville silt loams, shallow, 7 to 11 percent slopes, moderately eroded

Dodgeville, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 5
Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 56

limestone bedrock

Restrictive feature(s): lithic bedrock at 10 to 20 inches

Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: D

Drainage class: well drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 7 in	silt loam	moderate	1.13 to 1.28 in	6.6 to 8.4
Bt 7 to 16 in	silt loam	moderate	1.36 to 1.99 in	6.1 to 8.4
2R 16 to 60 in	bedrock	moderately rapid		7.9 to 8.4

Rockton, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 6
Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 48

limestone bedrock

Restrictive feature(s): lithic bedrock at 10 to 20 inches Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: D

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 7 in	silt loam	moderate	1.06 to 1.63 in	6.1 to 8.4
Bt 7 to 18 in	silt loam	moderate	1.65 to 2.43 in	6.1 to 8.4
2R 18 to 60 in	unweathered bedrock	moderately slow		



Available water

Available water

Fillmore County, Minnesota

Rp--Rockton and Dodgeville silt loams, shallow, 12 to 17 percent slopes, moderately eroded

Dodgeville, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 5
Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 56

limestone bedrock

**Restrictive feature(s): lithic bedrock at 10 to 20 inches

**Land capability, nonirrigated: 6e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: D

Drainage class: well drained Potential for frost action: low

Representative soil p	rofile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 7	in silt loam		moderate	1.13 to 1.28 in	6.6 to 8.4
Bt 7 to 16	6 in silt loam		moderate	1.36 to 1.99 in	6.1 to 8.4
2R 16 to 60	0 in bedrock		moderately rapid		7.9 to 8.4

Rockton, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 6
Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 48

limestone bedrock

Restrictive feature(s): lithic bedrock at 10 to 20 inches

Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: D

Representative so	il profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to	o 7 in	silt loam	moderate	1.06 to 1.63 in	6.1 to 8.4
Bt 7 to	o 18 in	silt loam	moderate	1.65 to 2.43 in	6.1 to 8.4
2R 18 to	o 60 in	unweathered bedrock	moderately slow		



Fillmore County, Minnesota

Rr--Rockton and Dodgeville silt loams, shallow, 18 to 35 percent slopes

Dodgeville

Extent: 45 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 5

Slope gradient: 18 to 35 percent Wind erodibility index (WEI): 56

Restrictive feature(s): lithic bedrock at 10 to 20 inches

Land capability, nonirrigated: 7e

Flooding: none

Hydric soil: no

Hydrologic group: D

Drainage class: well drained Potential for frost action: low

Representative	e soil profile:	Texture	Permeability	Available water capacity	рН
Ap	0 to 7 in	silt loam	moderate	1.13 to 1.28 in	6.6 to 8.4
Bt	7 to 16 in	silt loam	moderate	1.36 to 1.99 in	6.1 to 8.4
2R	16 to 60 in	bedrock	moderately rapid		7.9 to 8.4

Rockton

Extent: 45 percent of the unit Soil loss tolerance (T factor): 1

Landform(s): hills Wind erodibility group (WEG): 6

Slope gradient: 18 to 30 percent Wind erodibility index (WEI): 48

Parent material: loamy sediments over residuum over | Kw factor (surface layer) .32 | limestone bedrock


Restrictive feature(s): lithic bedrock at 10 to 20 inches

Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: D

Drainage class: well drained Potential for frost action: moderate

Representative soil profile	: Texture	Permeability	Available water capacity	рН
Ap 0 to 7 in	silt loam	moderate	1.06 to 1.63 in	6.1 to 8.4
Bt 7 to 18 in	silt loam	moderate	1.65 to 2.43 in	6.1 to 8.4
2R 18 to 60 in	unweathered bedrock	moderately slow		



Fillmore County, Minnesota

Sa--Schapville silty clay loam, 2 to 6 percent slopes

Schapville

Extent: 90 percent of the unit

Landform(s): hills

Slope gradient: 2 to 6 percent

Parent material: loess over residuum over shale bedrock

Restrictive feature(s): paralithic bedrock at 20 to 40 inche

Flooding: none

Ponding: none

Drainage class: somewhat poorly drained

Soil loss tolerance (T factor): 3

Wind erodibility group (WEG): 6

Wind erodibility index (WEI): 48

(w factor (curfoce layer) 24

Kw factor (surface layer) .24

Land capability, nonirrigated: 2e

Hydric soil: no

Hydrologic group: C/D

Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 17 in	silty clay loam	moderate	3.39 to 4.06 in	5.6 to 7.3
Bt1 17 to 26 in	silty clay loam	moderately slow	1.63 to 1.99 in	5.6 to 7.3
2Bt2 26 to 37 in	silty clay	slow	1.32 to 1.76 in	6.1 to 7.8
3Cr 37 to 60 in	weathered bedrock	slow		

Fillmore County, Minnesota

Sb--Schapville silty clay loam, 7 to 11 percent slopes, moderately eroded

Schapville, moderately eroded

Extent: 90 percent of the unit

Landform(s): hills

Slope gradient: 7 to 11 percent

Parent material: loess over residuum over shale bedrock

Restrictive feature(s): paralithic bedrock at 20 to 40 inche

Flooding: none Ponding: none

Drainage class: moderately well drained

Soil loss tolerance (T factor): 3

Wind erodibility group (WEG): 6

Wind erodibility index (WEI): 48

f f / / / f / / Of

Kw factor (surface layer) .24

Land capability, nonirrigated: 3e

Hydric soil: no

Hydrologic group: C

Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 8 in	silty clay loam	moderate	1.42 to 1.57 in	5.6 to 7.3
Bt1 8 to 22 in	silty clay loam	moderate	2.55 to 2.83 in	5.6 to 7.3
2Bt2 22 to 25 in	silty clay	slow	0.25 to 0.31 in	5.6 to 7.3
3Cr 25 to 60 in	weathered bedrock	slow		

Fillmore County, Minnesota

Sc--Schapville silty clay loam, 12 to 17 percent slopes, moderately eroded

Schapville, moderately eroded

Extent: 90 percent of the unit

Landform(s): hills

Slope gradient: 12 to 17 percent

Parent material: loess over residuum over shale bedrock

Restrictive feature(s): paralithic bedrock at 20 to 40 inche

Flooding: none Ponding: none

Drainage class: moderately well drained

Soil loss tolerance (T factor): 3

Wind erodibility group (WEG): 6

Wind erodibility index (WEI): 48

(w factor (curfoce layer) 24

Kw factor (surface layer) .24

Land capability, nonirrigated: 4e

Hydric soil: no

Hydrologic group: C

Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	pН
Ap 0 to 8 in	silty clay loam	moderate	1.42 to 1.57 in	5.6 to 7.3
Bt1 8 to 22 in	silty clay loam	moderate	2.55 to 2.83 in	5.6 to 7.3
2Bt2 22 to 25 in	silty clay	slow	0.25 to 0.31 in	5.6 to 7.3
3Cr 25 to 60 in	weathered bedrock	slow		

Fillmore County, Minnesota

Sd--Seaton and Port Byron silt loams, 2 to 6 percent slopes

Seaton

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 5

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 56
Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Hydrologic group: B

Flooding: none Hydric soil: no

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 8 in	silt loam	moderate	1.73 to 1.89 in	5.6 to 7.3
Bt 8 to 30 in	silt loam	moderate	4.41 to 4.85 in	4.5 to 7.3
C 30 to 60 in	silt loam	moderate	5.98 to 6.58 in	5.6 to 8.4

Port Byron

Ponding: none

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6
Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative	e soil profile:	Texture	Permeability	Available water capacity	рН
Ap	0 to 10 in	silt loam	moderate	2.17 to 2.36 in	5.1 to 8.4
Bw	10 to 26 in	silt loam	moderate	3.23 to 3.55 in	5.6 to 7.3
C 2	26 to 60 in	silt loam	moderate	6.77 to 7.45 in	5.6 to 8.4



Fillmore County, Minnesota

Se--Seaton and Port Byron silt loams, 7 to 11 percent slopes, moderately eroded

Seaton, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 5

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 56

Parent material: loess Kw factor (surface layer) .43

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	pН
Ap 0 to 8 in	silt loam	moderate	1.73 to 1.89 in	5.6 to 7.3
Bt 8 to 30 in	silt loam	moderate	4.41 to 4.85 in	4.5 to 7.3
C 30 to 60 in	silt loam	moderate	5 98 to 6 58 in	5.6 to 8.4

Port Byron, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 48
Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Ар	0 to 10 in	silt loam	moderate	2.17 to 2.36 in	5.1 to 8.4
Bw 1	0 to 26 in	silt loam	moderate	3.23 to 3.55 in	5.6 to 7.3
C 2	26 to 60 in	silt loam	moderate	6.77 to 7.45 in	5.6 to 8.4



Fillmore County, Minnesota

Sf--Seaton and Port Byron silt loams, 12 to 17 percent slopes, moderately eroded

Seaton, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 5

Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 56

Parent material: loess Kw factor (surface layer) .43

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	pН
Ap 0 to 8 in	silt loam	moderate	1.73 to 1.89 in	5.6 to 7.3
Bt 8 to 30 in	silt loam	moderate	4.41 to 4.85 in	4.5 to 7.3
C 30 to 60 in	silt loam	moderate	5 98 to 6 58 in	5.6 to 8.4

Port Byron, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6
Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Ар	0 to 10 in	silt loam	moderate	2.17 to 2.36 in	5.1 to 8.4
Bw 1	0 to 26 in	silt loam	moderate	3.23 to 3.55 in	5.6 to 7.3
C 2	26 to 60 in	silt loam	moderate	6.77 to 7.45 in	5.6 to 8.4



Fillmore County, Minnesota

Sg--Skyberg silt loam, 0 to 3 percent slopes

Skyberg

Extent: 85 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 0 to 3 percent Wind erodibility index (WEI): 48

Parent material: silty sediments over loamy till Kw factor (surface layer) .28

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2w

Flooding: none Hydric soil: no

Ponding: none Hydrologic group: C/D

Drainage class: somewhat poorly drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 12 in	silt loam	moderate	2.60 to 2.83 in	5.6 to 6.5
Bt1 12 to 24 in	silt loam	moderate	2.20 to 2.44 in	4.5 to 5.5
2Bt2 24 to 48 in	loam	moderately slow	3.36 to 4.56 in	5.1 to 7.3
2C 48 to 60 in	loam	moderately slow	1.06 to 1.54 in	7.4 to 7.8



Fillmore County, Minnesota

Ta--Tama and Downs silt loams, 0 to 1 percent slopes

Tama

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 1

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil prof	ile: Texture	Permeability	Available water capacity	рН
Ap,A,BA 0 to 17 ir	silt loam	moderate	3.72 to 4.06 in	5.1 to 7.3
Bt 17 to 38 in	silty clay loam	moderate	3.76 to 4.17 in	5.1 to 6.5
C 38 to 60 in	silt loam	moderate	3.97 to 4.41 in	5.6 to 7.3

Downs

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6
Slope gradient: 0 to 1 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 1

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 9 in	silt loam	moderate	1.90 to 2.08 in	5.1 to 7.3
E,BE 9 to 16 in	silt loam	moderate	1.28 to 1.42 in	5.1 to 6.0
Bt 16 to 45 in	silty clay loam	moderate	5.17 to 5.75 in	4.5 to 7.3
C 45 to 60 in	silt loam	moderate	2.69 to 2.99 in	5.6 to 7.3



Available water

Fillmore County, Minnesota

Tb--Tama and Downs silt loams, 2 to 6 percent slopes

Tama

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative	soil profile:	Texture	Permeability	Available water capacity	рН
Ap,A,BA	0 to 17 in	silt loam	moderate	3.72 to 4.06 in	5.1 to 7.3
Bt '	17 to 38 in	silty clay loam	moderate	3.76 to 4.17 in	5.1 to 6.5
C 3	38 to 60 in	silt loam	moderate	3.97 to 4.41 in	5.6 to 7.3

Downs

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6
Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	silt loam	moderate	1.90 to 2.08 in	5.1 to 7.3
E,BE 9 to 16 in	silt loam	moderate	1.28 to 1.42 in	5.1 to 6.0
Bt 16 to 45 in	silty clay loam	moderate	5.17 to 5.75 in	4.5 to 7.3
C 45 to 60 in	silt loam	moderate	2.69 to 2.99 in	5.6 to 7.3



Fillmore County, Minnesota

Te--Tama and Downs silt loams, 7 to 11 percent slopes, moderately eroded

Tama, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	5.1 to 7.3
Bt 10 to 35 in	silty clay loam	moderate	4.54 to 5.04 in	5.1 to 6.5
C 35 to 60 in	silt loam	moderate	4.46 to 4.96 in	5.6 to 7.3

Downs, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6

Slope gradient: 7 to 11 percent

Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .37
Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 3e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	silt loam	moderate	1.90 to 2.08 in	5.1 to 7.3
E,BE 9 to 16 in	silt loam	moderate	1.28 to 1.42 in	5.1 to 6.0
Bt 16 to 45 in	silty clay loam	moderate	5.17 to 5.75 in	4.5 to 7.3
C 45 to 60 in	silt loam	moderate	2.69 to 2.99 in	5.6 to 7.3



Fillmore County, Minnesota

Tg--Tama and Downs silt loams, 12 to 17 percent slopes, moderately eroded

Tama, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6

Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .32
Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 4e

Flooding: none

Hydric soil: no

Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	5.1 to 7.3
Bt 10 to 35 in	silty clay loam	moderate	4.54 to 5.04 in	5.1 to 6.5
C 35 to 60 in	silt loam	moderate	4.46 to 4.96 in	5.6 to 7.3

Downs, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6

Slope gradient: 12 to 17 percent Wind erodibility index (WEI): 48
Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 10 in	silt loam	moderate	2.07 to 2.26 in	5.1 to 7.3
Bt 10 to 35 in	silty clay loam	moderate	4.54 to 5.04 in	4.5 to 7.3
C 35 to 60 in	silt loam	moderate	4 46 to 4 96 in	5.6 to 7.3



Fillmore County, Minnesota

Tk--Tama and Downs silt loams, 18 to 35 percent slopes

Tama

Extent: 45 percent of the unit

Landform(s): loess hills

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 6

Slope gradient: 18 to 35 percent Wind erodibility index (WEI): 48

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 10 in	silt loam	moderate	2.17 to 2.36 in	5.1 to 7.3
Bt 10 to 35 in	silty clay loam	moderate	4.54 to 5.04 in	5.1 to 6.5
C 35 to 60 in	silt loam	moderate	4.46 to 4.96 in	5.6 to 7.3

Downs

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): loess hills Wind erodibility group (WEG): 6
Slope gradient: 18 to 30 percent Wind erodibility index (WEI): 48

Parent material: loess Kw factor (surface layer) .37

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 6e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: high

Representative s	soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0	to 10 in	silt loam	moderate	2.07 to 2.26 in	5.1 to 7.3
Bt 10	to 35 in	silty clay loam	moderate	4.54 to 5.04 in	4.5 to 7.3
C 35	to 60 in	silt loam	moderate	4.46 to 4.96 in	5.6 to 7.3



Fillmore County, Minnesota

TI--Mantorville and Wykoff loams, 0 to 1 percent slopes

Mantorville

Extent: 45 percent of the unit

Landform(s): terraces, till plains

Soil loss tolerance (T factor): 4

Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 48

Parent material: outwash

Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	pН
Ap 0 to 10 in	loam	moderate	1.97 to 2.17 in	5.1 to 7.3
Bw1 10 to 25 in	loam	moderate	2.30 to 2.92 in	5.1 to 7.3
2Bw2 25 to 40 in	gravelly loamy coarse sand	moderately rapid	0.30 to 2.09 in	5.1 to 7.3
2C 40 to 60 in	gravelly coarse sand	rapid	0.39 to 1.97 in	5.1 to 7.8

Wykoff

Extent: 45 percent of the unit

Landform(s): terraces, till plains

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 5

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 56

Parent material: outwash

Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	loam	moderate	1.54 to 2.08 in	5.6 to 7.3
Bt1 9 to 15 in	loam	moderate	0.77 to 1.12 in	5.1 to 6.5
Bt2 15 to 23 in	gravelly loam	moderate	0.87 to 1.50 in	5.1 to 6.5
BC 23 to 30 in	gravelly sandy loam	moderate	0.57 to 1.28 in	5.1 to 6.5
C 30 to 60 in	sand	moderate	2.39 to 5.39 in	5.6 to 6.5



I Amellahla matau I

Fillmore County, Minnesota

Tm--Mantorville and Wykoff loams, 2 to 6 percent slopes

Mantorville

Extent: 45 percent of the unit Soil loss tolerance (T factor): 4

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 48

Parent material: outwash Kw factor (surface layer) .24

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 10 in	loam	moderate	1.97 to 2.17 in	5.1 to 7.3
Bw1 10 to 25 in	loam	moderate	2.30 to 2.92 in	5.1 to 7.3
2Bw2 25 to 40 in	gravelly loamy coarse sand	moderately rapid	0.30 to 2.09 in	5.1 to 7.3
2C 40 to 60 in	gravelly coarse sand	rapid	0.39 to 1.97 in	5.1 to 7.8

Wykoff

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 5

Slope gradient: 2 to 6 percent Wind erodibility index (WEI): 56

Parent material: outwash Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 2e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 9 in	loam	moderate	1.54 to 2.08 in	5.6 to 7.3
Bt1 9 to 15 in	loam	moderate	0.77 to 1.12 in	5.1 to 6.5
Bt2 15 to 23 in	gravelly loam	moderate	0.87 to 1.50 in	5.1 to 6.5
BC 23 to 30 in	gravelly sandy loam	moderate	0.57 to 1.28 in	5.1 to 6.5
C 30 to 60 in	sand	moderate	2.39 to 5.39 in	5.6 to 6.5



Fillmore County, Minnesota

Tn--Mantorville and Wykoff loams, 7 to 17 percent slopes, moderately eroded

Mantorville, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 4

Landform(s): till plains Wind erodibility group (WEG): 6

Slope gradient: 7 to 17 percent Wind erodibility index (WEI): 48

Parent material: outwash Kw factor (surface layer) .24
Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 4e

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 10 in	loam	moderate	1.97 to 2.17 in	5.1 to 7.3
Bw1 10 to 25 in	loam	moderate	2.30 to 2.92 in	5.1 to 7.3
2Bw2 25 to 40 in	gravelly loamy coarse sand	moderately rapid	0.30 to 2.09 in	5.1 to 7.3
2C 40 to 60 in	gravelly coarse sand	rapid	0.39 to 1.97 in	5.1 to 7.8

Wykoff, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 5

Slope gradient: 7 to 17 percent Wind erodibility index (WEI): 56

Parent material: outwash Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4e


Flooding: none

Hydric soil: no

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: moderate

Representative soil profile:	Texture	Permeability	capacity	рН
Ap 0 to 9 in	loam	moderate	1.54 to 2.08 in	5.6 to 7.3
Bt1 9 to 15 in	loam	moderate	0.77 to 1.12 in	5.1 to 6.5
Bt2 15 to 23 in	gravelly loam	moderate	0.87 to 1.50 in	5.1 to 6.5
BC 23 to 30 in	gravelly sandy loam	moderate	0.57 to 1.28 in	5.1 to 6.5
C 30 to 60 in	sand	moderate	2.39 to 5.39 in	5.6 to 6.5



Available water

Fillmore County, Minnesota

To--Mantorville and Wykoff sandy loams, 0 to 1 percent slopes

Mantorville

Extent: 45 percent of the unit

Landform(s): terraces, till plains

Soil loss tolerance (T factor): 2

Wind erodibility group (WEG): 3

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 86

Parent material: outwash

Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3s

Flooding: none

Hydric soil: no

Ponding: none

Hydrologic group: A

Drainage class: somewhat excessively drained Potential for frost action: low

Representative soil profile	e: Texture	Permeability	Available water capacity	рН
Ap 0 to 7 in	sandy loam	moderately rapid	0.78 to 1.06 in	5.1 to 6.5
2Bw 7 to 17 in	sandy loam	moderately rapid	0.98 to 1.87 in	5.1 to 6.5
2C 17 to 60 in	gravelly sand	rapid	0.86 to 1.72 in	5.6 to 6.5

Wykoff

Extent: 45 percent of the unit

Landform(s): terraces, till plains

Soil loss tolerance (T factor): 5

Wind erodibility group (WEG): 3

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 86

Parent material: outwash

Kw factor (surface layer) .15

Restrictive feature(s): greater than 60 inches

Flooding: none

Hydric soil: no

Ponding: none Hydrologic group: B

Drainage class: excessively drained Potential for frost action: low

Representative soil profi	ile: Texture	Permeability	Available water capacity	рН
Ap 0 to 7 in	sandy loam	moderately rapid	0.78 to 0.92 in	5.1 to 7.3
Bt1 7 to 17 in	sandy loam	moderately rapid	0.98 to 1.18 in	4.5 to 6.0
Bt2 17 to 30 in	gravelly loamy sand	very rapid	0.26 to 0.52 in	4.5 to 6.0
C 30 to 60 in	sand	moderate	2.39 to 5.39 in	5.6 to 6.5



Fillmore County, Minnesota

Tp--Mantorville and Wykoff sandy loams, 2 to 6 percent slopes

Mantorville

Extent: 45 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): till plains Wind erodibility group (WEG): 3

Slope gradient:2 to 6 percentWind erodibility index (WEI):86Parent material:outwashKw factor (surface layer).17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 3e

Flooding: none

Hydric soil: no

Ponding: none Hydrologic group: A

Drainage class: somewhat excessively drained Potential for frost action: low

Representative soil profile.	Texture	Permeability	capacity	pН
Ap 0 to 7 in	sandy loam	moderately rapid	0.78 to 1.06 in	5.1 to 6.5
2Bw 7 to 17 in	sandy loam	moderately rapid	0.98 to 1.87 in	5.1 to 6.5
2C 17 to 60 in	gravelly sand	rapid	0.86 to 1.72 in	5.6 to 6.5

Wykoff

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains

Wind erodibility group (WEG): 3

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 86

Parent material: outwash Kw factor (surface layer) .15
Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 4s

Flooding: none

Hydric soil: no
Ponding: none

Hydrologic group: B

Drainage class: excessively drained Potential for frost action: low

Representative soil profi	le: Texture	Permeability	capacity	рН
Ap 0 to 7 in	sandy loam	moderately rapid	0.78 to 0.92 in	5.1 to 7.3
Bt1 7 to 17 in	sandy loam	moderately rapid	0.98 to 1.18 in	4.5 to 6.0
Bt2 17 to 30 in	gravelly loamy sand	very rapid	0.26 to 0.52 in	4.5 to 6.0
C 30 to 60 in	sand	moderate	2.39 to 5.39 in	5.6 to 6.5



L Avoilable water

Fillmore County, Minnesota

Tr--Mantorville and Wykoff sandy loams, 7 to 11 percent slopes, moderately eroded

Mantorville, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 2

Landform(s): till plains Wind erodibility group (WEG): 3

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 86

Parent material: outwash Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 4e

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: A

Drainage class: somewhat excessively drained Potential for frost action: low

Representative soil profile	: Texture	Permeability	Available water capacity	рН
Ap 0 to 7 in	sandy loam	moderately rapid	0.78 to 1.06 in	5.1 to 6.5
2Bw 7 to 17 in	sandy loam	moderately rapid	0.98 to 1.87 in	5.1 to 6.5
2C 17 to 60 in	gravelly sand	rapid	0.86 to 1.72 in	5.6 to 6.5

Wykoff, moderately eroded

Extent: 45 percent of the unit Soil loss tolerance (T factor): 5

Landform(s): till plains Wind erodibility group (WEG): 3

Slope gradient: 7 to 11 percent Wind erodibility index (WEI): 86

Parent material: outwash Kw factor (surface layer) .17

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated: 6s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: excessively drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 7 in	sandy loam	moderately rapid	0.78 to 0.92 in	5.1 to 7.3
Bt1 7 to 17 in	sandy loam	moderately rapid	0.98 to 1.18 in	4.5 to 6.0
Bt2 17 to 30 in	gravelly loamy sand	very rapid	0.26 to 0.52 in	4.5 to 6.0
C 30 to 60 in	sand	moderate	2.39 to 5.39 in	5.6 to 6.5



Fillmore County, Minnesota

W--Water

Water

Extent: 100 percent of the unit Soil loss tolerance (T factor):

Landform(s): Wind erodibility group (WEG):
Slope gradient: Wind erodibility index (WEI):

Parent material: Kw factor (surface layer)

Restrictive feature(s): greater than 60 inches Land capability, nonirrigated:

Flooding: Hydric soil:

Ponding: Hydrologic group:

Drainage class: Potential for frost action:

Representative soil profile:

Texture

Permeability

Available water capacity

PH

Wa--Waukegan silt loam, 0 to 1 percent slopes

Waukegan

Extent: 90 percent of the unit

Landform(s): outwash plains

Soil loss tolerance (T factor): 4

Wind erodibility group (WEG): 6

Slope gradient: 0 to 1 percent

Wind erodibility index (WEI): 48

Parent material: silty eolian deposits and/or outwash

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2s

Flooding: none Hydric soil: no
Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 15 in	silt loam	moderate	3.29 to 3.59 in	5.6 to 7.3
Bw 15 to 40 in	silt loam	moderate	5.04 to 5.54 in	5.1 to 7.3
2C 40 to 60 in	gravelly coarse sand	rapid	0.39 to 0.79 in	5.6 to 7.8



Fillmore County, Minnesota

Wb--Waukegan silt loam, 2 to 6 percent slopes

Waukegan

Extent: 90 percent of the unit

Landform(s): outwash plains

Soil loss tolerance (T factor): 4

Wind erodibility group (WEG): 6

Slope gradient: 2 to 6 percent

Wind erodibility index (WEI): 48

Parent material: silty eolian deposits and/or outwash

Kw factor (surface layer) .32

Restrictive feature(s): greater than 60 inches

Land capability, nonirrigated: 2e
Flooding: none

Hydric soil: no

Ponding: none Hydrologic group: B

Drainage class: well drained Potential for frost action: low

Representative soil profile:	Texture	Permeability	Available water capacity	рН
Ap 0 to 15 in	silt loam	moderate	3.29 to 3.59 in	5.6 to 7.3
Bw 15 to 40 in	silt loam	moderate	5.04 to 5.54 in	5.1 to 7.3
2C 40 to 60 in	gravelly coarse sand	rapid	0.39 to 0.79 in	5.6 to 7.8

This report provides a semitabular listing of some soil and site properties and interpretations that are valuable in communicating the concept of a map unit. The report also provides easy access to the commonly used conservation planning information in one place. The major soil components in each map unit are displayed. Minor components may be displayed if they are included in the database and are selected at the time the report is generated.

